



## TP-Link Deco X10 Doble banda (2,4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Blanco 2 Interno

**Marca :** TP-Link

**Código del producto:** DECO X10(3-PACK)

**Nombre del producto :** Deco X10

TP-Link Deco X10. Color del producto: Blanco, Tipo de antena: Interno, Tipo de producto: Enrutador de malla. Banda Wi-Fi: Doble banda (2,4 GHz / 5 GHz), Máximo estándar Wi-Fi: Wi-Fi 6 (802.11ax), Tasa de transferencia de datos WLAN (máx.): 1500 Mbit/s. Funciones de control parental: Hora de dormir, Perfiles personalizados, Family online time ranking, Tiempo en familia, Off time,..., Modos de funcionamiento: Router Mode, Access Point Mode. Ancho: 110 mm, Profundidad: 110 mm, Altura: 114 mm. Número de unidades incluidas: 3 pieza(s)



Design		Features	
Product type	Mesh router	Quality of Service (QoS) support	✓
Product colour *	White	Port forwarding	✓
LED indicators	Yes	BeamForming	✓
Antenna type *	Internal	DHCP client	✓
Maximum coverage	190 m²	DHCP server	✓
Reset button	✓	Universal Plug and Play (UPnP)	✓
Wireless LAN features		Parental control	✓
		Parental control features	Bedtime, Custom profiles, Family online time ranking, Family time, Off time, Pause the Internet, Professional content filter library, Time rewards
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	MU-MIMO technology	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	MIMO	✓
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Operating modes	Router Mode, Access Point Mode
WLAN data transfer rate (max) *	1500 Mbit/s	Ports & interfaces	
WLAN data transfer rate (first band)	300 Mbit/s	Ethernet LAN (RJ-45) ports *	2
WLAN data transfer rate (second band)	1201 Mbit/s	Operational conditions	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Operating temperature (T-T)	0 - 40 °C
Security algorithms	WPA, WPA2, WPA3	Storage temperature (T-T)	-40 - 60 °C
Number of guest networks (5 GHz)	1	Operating relative humidity (H-H)	10 - 90%
Number of guest networks (2.4 GHz)	1	Storage relative humidity (H-H)	5 - 90%
Dynamic IP	✓	Weight & dimensions	
Static IP	✓	Width	110 mm
IGMP proxy	✓	Depth	110 mm
IGMP snooping	✓	Height	114 mm
Tagged VLAN	✓	Packaging content	
Dynamic DNS (DDNS)	✓	AC adapter included	✓
Guest access	✓	Number of units included	3 pc(s)
Apps supported	TP-Link Deco	Ethernet cable	✓



4895252502480



4895252503166

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date