

TP-Link Archer AX12 router inalámbrico Ethernet rápido Doble banda (2,4 GHz / 5 GHz) Negro

Marca : TP-Link Familia de productos: Archer Código del producto: ARCHER AX12

Nombre del producto : Archer

AX12

TP-Link Archer AX12. Banda Wi-Fi: Doble banda (2,4 GHz / 5 GHz), Máximo estándar Wi-Fi: Wi-Fi 6 (802.11ax), Tasa de transferencia de datos WLAN (máx.): 1501 Mbit/s. Tipo de interfaz Ethernet LAN: Ethernet rápido, Estándares de red: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Algoritmos de seguridad: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3. Tipo de producto: Router de mesa, Color del producto: Negro. Certificados de cumplimiento: CE, Comisión Federal de Comunicaciones (FCC), RoHS





WAN connection		Security	
Ethernet WAN *	✓	Security algorithms	WPA-Enterprise, WPA-PSK, WPA2- Enterprise, WPA2-PSK, WPA3
DSL WAN *	×	Firewall	✓
SIM card slot *	×		
3G/4G USB modem compatibility *	×	URL filtering	/
Wireless LAN features		DMZ support	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Protocols	
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Universal Plug and Play (UPnP)	✓
WLAN data transfer rate (max) *	1501 Mbit/s	Design	
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Product colour	Black
		Product type *	Tabletop router
WLAN data transfer rate (first band)	300 Mbit/s	Certificates	
WLAN data transfer rate (second band)	1201 Mbit/s	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Network		Packaging content	
Ethernet LAN *	✓	Quick installation guide	✓
Ethernet LAN interface type *	Fast Ethernet	Antenna	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE	Antenna design *	External
Networking Standards	802.11g, IEEE 802.11n	Antennas quantity	4
Port forwarding	✓	Power	
Port triggering	✓	Power source type *	AC
Dynamic DNS (DDNS)	✓	71	AC .
Ports & interfaces		Operational conditions	0.4000
Ethernet LAN (RJ-45) ports *	4	Operating temperature (T-T)	0 - 40 °C -40 - 60 °C
USB port *	×	Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 60 °C 10 - 90%
·		Storage relative humidity (H-H)	5 - 90%
			= ==:=

Management features		Weight & dimensions	
Quality of Service (QoS) support	✓	Width	215 mm
Reset button	✓	Depth	117 mm
		Height	32 mm





4895252500875

4895252500882

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.