


CyberPower OLS6KERT5U sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 6 kVA 6000 W 9 salidas AC

Marca : CyberPower

Código del producto: OLS6KERT5U

Nombre del producto : OLS6KERT5U

CyberPower OLS6KERT5U. Topología UPS: Doble conversión (en línea), Capacidad de potencia de salida (VA): 6 kVA, Potencia de salida: 6000 W. Tipo de salida AC: Acoplador C13, Acoplador C19, Terminal, Conector: Acoplador C13, Cantidad de salidas AC: 9 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo típico de respaldo a carga completa: 5.6 min, Tiempo típico de respaldo a media carga: 17.7 min. Factor de forma: Tower, Color del producto: Negro, Material de la cubierta: Metal. Certificados de cumplimiento: CE, RoHS



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at full load	5.6 min
Output power capacity *	6 kVA	Typical backup time at half load	17.7 min
Output power *	6000 W	Battery recharge time	4 h
Waveform *	Pure sine	Charging current	4 A
Input operation voltage (min) *	110 V	Hot-swap battery	✓
Input operation voltage (max) *	300 V	Design	
Input frequency *	50/60 Hz	Form factor *	Tower
Output operation voltage (min)	200 V	Housing material	Metal
Output operation voltage (max)	240 V	Rack capacity	5U
Output frequency	50/60 Hz	Built-in fan	✓
Surge energy rating	1335 J	Product colour *	Black
Heat dissipation	1777 BTU/h	Display type	LCD
Efficiency (ECO mode)	98%	Operational conditions	
Input power factor	0.99	Operating temperature (T-T)	0 - 40 °C
Output power factor	1	Storage temperature (T-T)	-15 - 45 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
ECO mode	✓	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Operating altitude	0 - 1500 m
Output voltage Total Harmonic Distortion (THD)	2%	Non-operating altitude	0 - 1500 m
Input current Total Harmonic Distortion (THD)	1.5%	Certificates	
EMI/RFI noise filtering	✓	Compliance certificates	CE, RoHS
Noise level	62 dB	Packaging content	
Power protection features	Overload	Cables included	USB cable
Carrying handle(s)	✗	Manual	✓
Audible alarm(s)	✓	Sustainability	
Audible alarm modes	Battery replacement, Fault, Overload alarm	Sustainability compliance	✓

Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler, C19 coupler, Terminal	Width	433 mm
Power plug	C13 coupler	Depth	661 mm
AC outlets quantity	9 AC outlet(s)	Height	213.5 mm
USB port	✓	Weight	75 kg
RS-232 ports	1	Packaging data	
Battery		Package width	575 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	890 mm
		Package height	489 mm
		Package weight	94 kg
		Package type	Box

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date