

CyberPower OLS10KERT5U sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 10 kVA 10000 W 9 salidas AC

Marca : CyberPower

Código del producto: OLS10KERT5U

Nombre del producto : OLS10KERT5U

CyberPower OLS10KERT5U. Topología UPS: Doble conversión (en línea), Capacidad de potencia de salida (VA): 10 kVA, Potencia de salida: 10000 W. Tipo de salida AC: Acoplador C13, Acoplador C19, Terminal, Conector: Acoplador C13, Cantidad de salidas AC: 9 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo típico de respaldo a carga completa: 2.9 min, Tiempo típico de respaldo a media carga: 11.2 min. Factor de forma: Tower, Color del producto: Negro, Material de la cubierta: Metal. Certificados de cumplimiento: CE, RoHS



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at full load	2.9 min
Output power capacity *	10 kVA	Typical backup time at half load	11.2 min
Output power *	10000 W	Battery recharge time	4 h
Waveform *	Pure sine	Charging current	4 A
Input operation voltage (min) *	110 V	Hot-swap battery	✓
Input operation voltage (max) *	300 V	Design	
Input frequency *	50/60 Hz	Form factor *	Tower
Output operation voltage (min)	200 V	Housing material	Metal
Output operation voltage (max)	240 V	Rack capacity	5U
Output frequency	50/60 Hz	Built-in fan	✓
Surge energy rating	1335 J	Product colour *	Black
Heat dissipation	2047 BTU/h	Display type	LCD
Efficiency (ECO mode)	98%	Compatibility	BPS240V9ART3U
Input power factor	0.99	Operational conditions	
Output power factor	1	Operating temperature (T-T)	0 - 40 °C
Crest factor	3:1	Storage temperature (T-T)	-15 - 45 °C
ECO mode	✓	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	3%	Operating altitude	0 - 1500 m
Input current Total Harmonic Distortion (THD)	1.5%	Non-operating altitude	0 - 1500 m
EMI/RFI noise filtering	✓	Certificates	
Noise level	62 dB	Compliance certificates	CE, RoHS
Power protection features	Overload	Packaging content	
Carrying handle(s)	✗	Cables included	USB cable
Audible alarm(s)	✓	Manual	✓
Audible alarm modes	Battery replacement, Fault, Overload alarm		

Ports & interfaces		Sustainability	
AC outlet types	C13 coupler, C19 coupler, Terminal	Sustainability compliance	✓
Power plug	C13 coupler	Weight & dimensions	
AC outlets quantity	9 AC outlet(s)	Width	433 mm
USB port	✓	Depth	661 mm
RS-232 ports	1	Height	213.5 mm
Battery		Weight	80 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
		Package width	575 mm
		Package depth	890 mm
		Package height	489 mm
		Package weight	99 kg
		Package type	Box

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date