



DELL S Series S2425H LED display 60.5 cm (23.8") 1920 x 1080 Píxeles Full HD LCD Negro, Plata

Marca : DELL

Familia de productos: S
Series

Código del producto: S2425H

Nombre del producto :
S2425H

- 60.5cm (23.8") Full HD 1920 x 1080 Edge LED IPS

- 8ms, 16:9, 250cd/m², 1500:1

- HDMI

60.5cm (23.8") Full HD 1920 x 1080 Edge LED IPS, 16:9, 250cd/m², 16.78M, 8ms, 178°/178°, 1500:1

DELL S Series S2425H LED display 60.5 cm (23.8") 1920 x 1080 Píxeles Full HD LCD Negro, Plata:

Un monitor FHD de 24 pulgadas que optimiza la comodidad ocular y cuenta con unos impresionantes efectos visuales con una acústica excepcional en un diseño inspirado en el estilo de vida.

DELL S Series S2425H. Diagonal de la pantalla: 60.5 cm (23.8"), Resolución de la pantalla: 1920 x 1080 Píxeles, Tipo HD: Full HD, Tecnología de visualización: LCD, Tiempo de respuesta: 8 ms, Relación de aspecto nativa: 16:9, Ángulo de visión, horizontal: 178°, Ángulo de visión, vertical: 178°. Altavoces incorporados. montaje VESA. Color del producto: Negro, Plata



Display		Power	
Display diagonal *	60.5 cm (23.8")	Energy efficiency class (SDR) *	D
Display resolution *	1920 x 1080 pixels	Energy consumption (SDR) per 1000 hours *	15 kWh
HD type *	Full HD	Power consumption (typical) *	14.5 W
Native aspect ratio *	16:9	Power consumption (standby) *	0.4 W
Display technology *	LCD	Power consumption (max)	42 W
Panel type *	IPS	Power consumption (off)	0.3 W
LED backlight	✓	AC input voltage	100 - 240 V
Backlight type	Edge LED	AC input frequency	50/60 Hz
Touchscreen *	✗	Input current	1.5 A
Display brightness (typical)	250 cd/m²	Power supply type	Internal
Response time *	8 ms	Energy efficiency scale	A to G
Anti-glare screen	✓	European Product Registry for Energy Labelling (EPREL) code	1856260
Screen shape *	Flat	Operational conditions	
Supported video modes	480p, 576p, 1080i, 1080p	Operating temperature (T-T)	0 - 40 °C
Contrast ratio (typical) *	1500:1	Storage temperature (T-T)	-20 - 60 °C
Maximum refresh rate *	100 Hz	Operating relative humidity (H-H)	10 - 80%
Viewing angle, horizontal	178°	Storage relative humidity (H-H)	5 - 90%
Viewing angle, vertical	178°	Operating altitude	0 - 5000 m
Display number of colours *	16.78 million colours	Non-operating altitude	5000 - 12192 m
Response time (fast)	5 ms	Weight & dimensions	
Pixel pitch	0.2745 x 0.2745 mm	Width (with stand)	537.6 mm
Pixel density	93 ppi	Depth (with stand)	163 mm
Viewable size, horizontal	52.7 cm	Height (with stand)	411.7 mm
Viewable size, vertical	29.6 cm	Weight (with stand)	3.85 kg
Surface hardness	3H	Width (without stand)	537.6 mm
sRGB coverage (typical)	99%	Depth (without stand)	58.9 mm
Performance		Height (without stand)	313.7 mm
NVIDIA G-SYNC *	✗		

Performance		Weight & dimensions	
AMD FreeSync *	✗	Weight (without stand)	3.29 kg
Flicker-free technology	✓	Bezel width (side)	5.3 mm
Low Blue Light technology	✓	Bezel width (top)	5.3 mm
		Bezel width (bottom)	1.2 cm
Multimedia		Packaging data	
Number of speakers	2	Package weight	5.92 kg
RMS rated power	10 W	Packaging content	
Built-in speaker(s) *	✓	Stand included	✓
Built-in camera *	✗	Cables included	AC, HDMI
Design		Quick start guide	✓
Market positioning *	Office	HDMI cable length	1.8 m
Product colour *	Black, Silver	Sustainability	
Front bezel colour	Black	Sustainability compliance	✓
Feet colour	Silver	Sustainability certificates	ENERGY STAR
Ports & interfaces		Doesn't contain	PVC/BFR
Built-in USB hub *	✗	Carbon footprint	
HDMI *	✓	Total carbon footprint (kg of CO2e)	157
HDMI ports quantity	2	Carbon emissions, manufacturing (kg of CO2e)	71
HDMI version	1.4	Carbon emissions, logistics (kg of CO2e)	11
Headphone out *	✗	Carbon emissions, energy usage (kg of CO2e)	72
HDCP	✓	Carbon emissions, end-of-life (kg of CO2e)	3
HDCP version	1.4	Total carbon emissions, w/o use phase (kg of CO2e)	85
AC (power) in	✓	PAIA version	GaBi version 1, 2024
Ergonomics		Other features	
VESA mounting *	✓	Compliance certificates	RoHS
Panel mounting interface	100 x 100 mm		
Cable lock slot *	✓		
Cable lock slot type	Kensington		
Height adjustment *	✗		
Tilt adjustment	✓		
Tilt angle range	-5 - 21°		
On Screen Display (OSD)	✓		
Plug and Play	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date