

## Dahua Technology DH-P3B-PV cámara de vigilancia Torreta Cámara de seguridad IP Exterior 2304 x 1296 Pixeles Techo/pared

Marca : Dahua Technology Código del producto: DH-P3B-PV

Nombre del producto : DH-P3B-PV

Dahua Technology DH-P3B-PV. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Inalámbrico y alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Torreta. Ángulo de rotación: 180°, Ángulo de visión del objetivo, horizontal: 87°, Ángulo de visión del objetivo, vertical: 44°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Distancia de visión nocturna: 30 m, Tipo de LED: IR/Blanco

| Performance   |  | Video   |  |  |  |
|---|--|---|--|--|--|
| Type * IP security camera  Placement supported * Outdoor  Connectivity technology * Wired & Wireless                        | Outdoor  | Bit rate<br>Digital Wide Dynamic Range<br>(DWDR)                              | 80 kbps-4096 kbps  |  |  |
| Auto-tracking   | uto-tracking 🗸                                     |   | Audio  |  |  |
| Wide Dynamic Range (WDR)  | ✓  | Built-in speaker(s)   | ✓  |  |  |
| Day/night mode  | ✓  | Built-in microphone   | ✓  |  |  |
| Built-in light  | ✓  | Voice codecs  | G.711a   |  |  |
| Design  |  | Network   |  |  |  |
| Form factor * Mounting type * Product colour * Housing material International Protection (IP) code                          | Turret<br>Ceiling/wall<br>White<br>Plastic<br>IP66 | Ethernet LAN * Ethernet interface type Wi-Fi * Wi-Fi standards                | Fast Ethernet  802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6 (802.11ax) |  |  |
| Camera  |  | Bluetooth *   | ✓  |  |  |
| Lens viewing angle, horizontal 87° Lens viewing angle, vertical 44° Lens viewing angle, diagonal 105 Tilt angle range 0 - 9 |  | Storage   |  |  |  |
|   |  | Card reader integrated<br>Compatible memory cards<br>Maximum memory card size | MicroSD (TransFlash) 256 GB  |  |  |
|   |  | Ports & interfaces  |  |  |  |
| Camera shutter type   | Electronic   | Ethernet LAN (RJ-45) ports  | 1  |  |  |
| Camera shutter speed  | 1/3 s-1/100,000 s                                  | Security  |  |  |  |
| Adjustment shutter speed  Image sensor  | ·  |   | Human detection, Vehicle detection                                     |  |  |
| Optical sensor size   | 25.4 / 2.7 mm (1 / 2.7")                           | Power   |  |  |  |
| Sensor type *   | CMOS   | Power source type *   | DC   |  |  |
| Lens system   |  | Power consumption (typical)   | 1.56 W   |  |  |
| Maximum aperture number   | 1.6  | Power consumption (max) DC output voltage                                     | 4.56 W<br>12   |  |  |
| Night vision  |  | Operational conditions  |  |  |  |
| Night vision * Night vision distance LED type   | ✓<br>30 m<br>IR/White                              | Operating temperature (T-T) Operating relative humidity (H-H)                 | -20 - 50 °C<br>0 - 95%   |  |  |
| Number of illumination LEDs   | 4  | System requirements   |  |  |  |
| Video   |  | Mobile operating systems supported  | d Android, iOS   |  |  |
| Maximum resolution * Total megapixels * Video compression formats Frame rate Video streaming                                | 2304 x 1296 pixels 3 MP H.265 30 fps               | Weight & dimensions  Width Depth Height Weight                                | 116 mm<br>138 mm<br>139 mm<br>425 g                                    |  |  |
| video streaming   | •  | - J···-   | - 3  |  |  |

| _   |     |     |      |       |
|-----|-----|-----|------|-------|
| Dar | ran | ina | con  | tent  |
| u   | Nuy | шч  | COII | CCIIC |

Number of cameras \*

1

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date

