



## Dahua Technology DH-H3A cámara de vigilancia Domo Cámara de seguridad IP Interior 2304 x 1296 Pixeles Techo/pared

**Marca :** Dahua Technology

**Código del producto:** DH-H3A

**Nombre del producto :** DH-H3A

Dahua Technology DH-H3A. Tipo: Cámara de seguridad IP, Colocación compatible: Interior, Tecnología de conectividad: Inalámbrico y alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Domo. Ángulo de campo de visión (FOV): 88°, Ángulo de rotación: 180°, Ángulo de visión del objetivo, horizontal: 73°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 3.2 mm (1 / 3.2"). Distancia de visión nocturna: 10 m

Performance		Video	
Type *	IP security camera	Digital Wide Dynamic Range (DWDR)	✓
Placement supported *	Indoor	<b>Audio</b>	
Connectivity technology *	Wired & Wireless	Built-in speaker(s)	✓
Auto-tracking	✓	Built-in microphone	✓
Wide Dynamic Range (WDR)	✓	Voice codecs	G.711a
Day/night mode	✓	<b>Network</b>	
Design		Ethernet LAN *	✓
Form factor *	Dome	Wi-Fi *	✓
Mounting type *	Ceiling/wall	Wi-Fi standards	Wi-Fi 4 (802.11n), Wi-Fi 6 (802.11ax)
Product colour *	White	Bluetooth *	✓
Housing material	Plastic	Storage	
Camera		Card reader integrated	✓
Field of view (FOV) angle	88°	Compatible memory cards	SD
Angle of rotation	180°	Maximum memory card size	256 GB
Lens viewing angle, horizontal	73°	Ports & interfaces	
Lens viewing angle, vertical	41°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, diagonal	88°	Microphone in	✓
Tilt angle range	-5 - 80°	Security	
Pan range	0 - 365°	Video motion detection	✓
Camera shutter type	Electronic	Intelligent Video Surveillance (IVS) system features	Human detection
Camera shutter speed	1/3 -1/100000	Power	
Image sensor		Power source type *	DC
Number of sensors	1	Power consumption	1.6 mA
Optical sensor size	25.4 / 3.2 mm (1 / 3.2")	Power consumption (max)	3.6 W
Sensor type *	CMOS	Operational conditions	
Lens system		Operating temperature (T-T)	-10 - 45 °C
Number of lenses *	1	Operating relative humidity (H-H)	0 - 95%
Maximum aperture number	2	Weight & dimensions	
Night vision		Width	77.8 mm
Night vision *	✓	Depth	108.1 mm
Night vision distance	10 m	Weight	195 g
Video		Packaging content	
Maximum resolution *	2304 x 1296 pixels	Number of cameras *	1
Total megapixels *	3 MP	Memory card included	MicroSD
Video formats supported	H.265		
Bit rate	H.265: 80 kbps-4096 kbps		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date