

Dahua Technology P5B-PV Esférico Cámara de seguridad IP Interior y exterior 2880 x 1620 Pixeles Techo/pared

Marca : Dahua Technology Código del producto: DH-P5B-PV

Nombre del producto: P5B-PV

Dahua Technology P5B-PV. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Inalámbrico y alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Esférico. Ángulo de visión del objetivo, horizontal: 78°, Ángulo de visión del objetivo, vertical: 40°, Ángulo de visión de la lente, diagonal: 93°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 3 mm (1 / 3"). Distancia de visión nocturna: 30 m

Performance		Audio	
Type *	IP security camera	Voice codecs	G.711a
Placement supported *	Indoor & outdoor	Network	
Connectivity technology *	Wired & Wireless	Ethernet LAN *	✓
Design		Ethernet interface type	Fast Ethernet
Form factor *	Spherical	Wi-Fi *	✓
Mounting type * Product colour *	Ceiling/wall White	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6 (802.11ax)
Housing material	Plastic	Bluetooth *	×
International Protection (IP) code	IP66	Storage	
Camera		Built-in HDD *	×
Lens viewing angle, horizontal	78°	Card reader integrated	✓
Lens viewing angle, vertical Lens viewing angle, diagonal	40° 93°	Compatible memory cards	MicroSD (TransFlash)
Tilt angle range	0 - 90°	Maximum memory card size	256 GB
Pan range	0 - 355°	Ports & interfaces	
Camera shutter type	Electronic	Ethernet LAN (RJ-45) ports	1
Camera shutter speed	1/3 - 1/100000 s	Security	
Image sensor		Video motion detection	✓
Optical sensor size Sensor type *	25.4 / 3 mm (1 / 3") CMOS	Intelligent Video Surveillance (IVS) system features	Human detection, Vehicle detection
Lens system		Management features	
Number of lenses *	1	Smartphone/tablet remote support	✓
Maximum aperture number	1.6	Management software	DMSS
Night vision		Power	
Night vision *	✓	Power source type *	DC
Night vision distance	30 m	Power consumption (typical)	1.68 W
Number of illumination LEDs	2	Power consumption (max)	4.56 W
Video		DC output voltage	12
Maximum resolution *	2880 x 1620 pixels	Operational conditions	
Total megapixels *	5 MP	Operating temperature (T-T)	-20 - 50 °C 0 - 95%
Supported graphics resolutions	H.265 640 x 360, 2880 x 1620 30 fps H.265: 80 kbps-4096 kbps	Operating relative humidity (H-H)	0 - 95%
		System requirements	
Bit rate		Mobile operating systems supported Android, iOS	
	n.203. ou kups-4090 kups		
Digital Wide Dynamic Range	n.203. 60 kbps-4090 kbps	Weight & dimensions	
(DWDR)	•	Width	138 mm
(DWDR) Smart IR	·	Width Depth	116 mm
(DWDR) Smart IR Audio	•	Width Depth Height	116 mm 139 mm
(DWDR) Smart IR Audio Built-in speaker(s)	•	Width Depth Height Weight	116 mm
(DWDR) Smart IR Audio	<i>* *</i>	Width Depth Height	116 mm 139 mm

	CONTANT
Packaging	COLLEGIE

Number of cameras *

1

