

## Dahua Technology DH-IPC-HMW3230N-M-DAE-0600B cámara de vigilancia Cámara de seguridad IP Exterior 1920 x 1080 Pixeles

Marca: Dahua Technology

Código del producto: DH-IPC-HMW3230N-M-DAE-0600B

Nombre del producto : DH-IPC-HMW3230N-M-

DAE-0600B

Dahua Technology DH-IPC-HMW3230N-M-DAE-0600B. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Color del producto: Negro, Material de la cubierta: Metal, Código IP (International Protection): IP67. Ángulo de visión del objetivo, horizontal: 55°, Ángulo de visión del objetivo, vertical: 31°, Ángulo de visión de la lente, diagonal: 62°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Distancia focal fija: 6 mm

Performance		Video	
Type * Placement supported * Connectivity technology * Wide Dynamic Range (WDR)	IP security camera Outdoor Wired ✓	Back Light Compensation (BLC) Highlight Compensation (HLC) Digital Wide Dynamic Range (DWDR)	* * *
Day/night mode	<b>✓</b>	Audio	
Design		Signal-to-Noise Ratio (SNR)	65 dB
Product colour *	Black	Built-in microphone	<b>✓</b>
Housing material	Metal	Network	
International Protection (IP) code	IP67	Ethernet LAN *	1
Camera		Ethernet interface type	Fast Ethernet HTTP;HTTPs;TCP;ARP;RTSP;RTP;UDP;RTCP;SMTP;
Minimum illumination Lens viewing angle, horizontal	0 lx 55°	Supported network protocols	FTP;DHCP;DNS;DDNS;PPPOE;IPv4/v6;QoS;UPnP; NTP;Bonjour;IEEE 802.1x;Multicast;ICMP;IGMP;S NMP;TLS
Lens viewing angle, vertical	31° 62°	Wi-Fi *	×
Lens viewing angle, diagonal White balance	Auto, Manual	Bluetooth *	<b>X</b>
Camera shutter type	Electronic	Number of users Streaming method	20 user(s) Multicast, Unicast
Camera shutter speed	1/3 - 1/100000 s	Storage	
Image sensor		Built-in HDD *	×
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Card reader integrated	· ·
Progressive scan	✓	Compatible memory cards	MicroSD (TransFlash)
Sensor type *	CMOS	Ports & interfaces	
Lens system		Ethernet LAN (RJ-45) ports	1
Minimum aperture number	2	Power	
Fixed focal length	6 mm	Power source type *	DC, PoE
Night vision		Power consumption (typical)	1.3 W
Night vision *	<b>✓</b>	Power consumption (max)	2.4 W
Night vision distance	30 m	DC output voltage	12
LED type	IR	Operational conditions	
Video		Operating temperature (T-T)	-30 - 60 °C
Maximum resolution *	1920 x 1080 pixels	Operating relative humidity (H-	H) 0 - 95%
Total megapixels *	2 MP	Weight & dimensions	
Video compression formats	H.264, H.264B, H.264H, H.265, M- JPEG	Width	107 mm
Supported video modes	1080p	Depth	82 mm
Frame rate	30 fps	Height	68 mm
Noise reduction	<b>✓</b>	Weight	395 g
Noise reduction technology	3D noise reduction	Packaging data	
Gain control type	Auto/Manual Constant Bit Rate (CBR)/Variable Bit	Package weight	550 g
Bit rate control	Rate (VBR)		

	CONTANT
Packaging	COLLEGIE

Number of cameras \*

1

