

## Dahua Technology DH-IPC-T1E20 cámara de vigilancia Domo Cámara de seguridad IP Interior y exterior 1920 x 1080 Pixeles Techo/pared

Marca : Dahua Technology Código del producto: DH-IPC-T1E20

Nombre del producto : DH-IPC-T1E20

Dahua Technology DH-IPC-T1E20. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Negro, Blanco, Factor de forma: Domo. Iluminación mínima: 0.005 Lux, Ángulo de rotación: 360°, Ángulo de inclinación: 0 - 78°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 3.2 mm (1 / 3.2"). Distancia de detección: 44.7 m, Distancia de observación: 17.9 m, Distancia de reconocimiento: 8.9 m

Performance		Video	
Type *	IP security camera	Gain control type	Auto
Placement supported *	Indoor & outdoor	Privacy masking	✓
Connectivity technology * Wide Dynamic Range (WDR)	Wired ✓	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Day/night mode	<b>√</b>	Bit rate	12-4096
Plug and Play	<b>√</b>	Back Light Compensation (BLC)	✓
Design		Highlight Compensation (HLC)	✓
Form factor *	Dome	Digital Wide Dynamic Range (DWDR)	✓
Mounting type *	Ceiling/wall	Region of Interest (ROI) encoding	<b>✓</b>
Product colour *	Black, White	Smart IR	·
Housing material	Plastic	Audio	
International Protection (IP) code	IP67		E.C. J.D.
Camera		Signal-to-Noise Ratio (SNR)	56 dB
Minimum illumination	0.005 lx	Network	
Angle of rotation	360°	Ethernet LAN *	✓
Tilt angle range	0 - 78°	Ethernet interface type	Fast Ethernet
Pan range White balance	0 - 360° Auto, Manual, Natural, Outdoor,	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; P2P
Camera shutter type	Regional custom, Street lamp Electronic	Wi-Fi *	×
Camera shutter speed	1/3 - /100000 s	Bluetooth *	×
Number of Privacy masking areas	4	Storage	
Image sensor		Built-in HDD *	×
Optical sensor size	25.4 / 3.2 mm (1 / 3.2")	ROM capacity	16 MB
Progressive scan	✓	RAM capacity	64 MB
Sensor type *	CMOS	Ports & interfaces	
Lens system		Ethernet LAN (RJ-45) ports	1
Number of lenses *	1	Security	
Detect distance	44.7 m	Video motion detection	✓
Observe distance Recognize distance	17.9 m 8.9 m	Mirror	✓
Lens diameter	2.8 mm	Power	
Identify distance	4.5 m	Power source type *	DC, PoE
Closest focusing distance	0.5 m	Power consumption (typical)	1.2 W
Night vision		Power consumption (max)	4 W
Night vision *	<b>✓</b>	Power consumption (Power over	2.1 W
Night vision distance	30 m	Ethernet (PoE)) DC output voltage	12
LED type	IR		
Number of illumination LEDs	2	Operational conditions	40 50 %
		Operating temperature (T-T)	-40 - 50 °C

Video		Operational conditions	
Maximum resolution * Total megapixels *	1920 x 1080 pixels 2 MP	Storage temperature (T-T)  Weight & dimensions	-40 - 60 °C
Frame rate 30 Noise reduction		Height Diameter Weight	103.2 mm 11 cm 240 g
	3D noise reduction	Packaging data Package weight	380 g
		Packaging content	
		Number of cameras *	1

