

## Dahua Technology WizSense DH-IPC-HDBW2241E-S cámara de vigilancia Esférico Cámara de seguridad IP Exterior 1920 x 1080 Pixeles Techo

Marca: Dahua Technology

Familia de productos: WizSense Código del producto: DH-IPC-

HDBW2241E-S

Nombre del producto: DH-

IPC-HDBW2241E-S

Dahua Technology WizSense DH-IPC-HDBW2241E-S. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Esférico. Ángulo de rotación: 355°, Ángulo de inclinación: 0 - 65°, Rango de paneo: 0 - 355°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Distancia de visión nocturna: 30 m, Tipo de LED: IR





Performance		Video	
**	IP security camera Outdoor	Bit rate Back Light Compensation (BLC)	H.265: 12 kbps-6144 kbps ✓
Connectivity technology * Wide Dynamic Range (WDR)	Wired	Highlight Compensation (HLC)	✓
Day/night mode	<b>,</b>	Audio	
Dynamic range	120 dB	Audio formats supported Signal-to-Noise Ratio (SNR)	G.711 A-law, G.726, PCM 56 dB
Design		Built-in microphone	<b>✓</b>
Form factor * Mounting type *	Spherical Ceiling	Network	
Product colour * International Protection (IP) code	White IP67	Ethernet LAN * Ethernet interface type	✓ Fast Ethernet, Gigabit Ethernet
Camera		Wi-Fi *	×
Angle of rotation Tilt angle range	355° 0 - 65°	Bluetooth * Number of users	X 6 user(s)
Pan range	0 - 355°	Storage	
Auto flip	✓	Built-in HDD *	×
Camera shutter type Camera shutter speed Adjustment shutter speed Number of Privacy masking areas	Electronic 1/3 - 1/10000 s Auto/Manual 4	Card reader integrated Compatible memory cards Maximum memory card size ROM capacity	✓ MicroSD (TransFlash) 256 GB 128 MB
Image sensor		RAM capacity	128 MB
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Ports & interfaces	
Progressive scan	✓ CMOC	Ethernet LAN (RJ-45) ports	1
Sensor type *	CMOS	Management features	
Lens system		Web-based management	✓
Maximum aperture number	1.6	Web browser	✓

Night vision		Power	
Night vision *	<b>✓</b>	Power source type *	DC, PoE
Night vision distance	30 m	Power consumption (typical)	1.9 W
LED type	IR	Power consumption (max)	5.6 W
Number of illumination LEDs	3	Power consumption (Power over Ethernet (PoE))	2.5 W
Video		DC output voltage	12
Maximum resolution * Total megapixels * Video compression formats Frame rate	1920 x 1080 pixels 2 MP H.264, H.264B, H.265 30 fps  ✓	Operational conditions	
		Operating temperature (T-T)	-40 - 60 °C
		Storage temperature (T-T)	0 - 95 °C
Video streaming		Weight & dimensions	
Noise reduction	<b>✓</b>	Height	81 mm
Noise reduction technology	3D noise reduction	Diameter	11 cm
Gain control type	Auto	Weight	340 g
Flip & mirror	✓	Packaging data	
Privacy masking	<b>/</b>	Package weight	490 g
		Packaging content	
		Number of cameras *	1

