



ATEN 2L-7DA3H cable HDMI 0.3 m HDMI Tipo A (Estándar) Negro, Oro

Marca : ATEN

Código del producto: 2L-7DA3H



Nombre del producto : Cable HDMI True 4K de alta velocidad con Ethernet de 0,3 m

- Transmisión óptima de señal hasta 4K real (4096 x 2160 / 3840 x 2160 @ 60 Hz; 4:4:4)
 - HDMI (3D, Color profundo, 4K); compatible con HDCP 2.2
 - Conectores chapados en oro para transmisiones fiables
 - Disponible en 0,3 m
- Cable HDMI True 4K de alta velocidad con Ethernet de 0,3 m

ATEN 2L-7DA3H cable HDMI 0.3 m HDMI Tipo A (Estándar) Negro, Oro:

El cable HDMI de alta velocidad con Ethernet de ATEN ofrece una interfaz sin comprimir totalmente digital para señales de audio y de vídeo, lo que garantiza una transmisión de señal fiable a resoluciones hasta 4K real (4096 x 2160 / 3840 x 2160 @ 60 Hz; 4:4:4). Nuestros cables están dotados de hilo de cobre teñido de alta calidad para ofrecer un vídeo más definido y más calidad de imagen.

ATEN 2L-7DA3H. Longitud de cable: 0.3 m, Conector 1: HDMI Tipo A (Estándar), Género del conector 1: Macho, Conector 2: HDMI Tipo A (Estándar), Género del conector 2: Macho, Contactos del conector chapado: Oro, 3D, Color del producto: Negro, Oro

Features		Features	
Cable length *	0.3 m	Plug and Play	✓
Connector 1 *	HDMI Type A (Standard)	Operational conditions	
Connector 2 *	HDMI Type A (Standard)	Operating temperature (T-T)	0 - 80 °C
Connector 1 gender *	Male	Certificates	
Connector 2 gender *	Male	Compliance certificates	RoHS
Connector 1 form factor	Straight	Weight & dimensions	
Connector 2 form factor	Straight	Cable diameter	6 mm
Product colour *	Black, Gold	Weight	54 g
3D	✓	Packaging data	
Supported graphics resolutions	1920 x 1080 (HD 1080), 3840 x 2160, 4096 x 2160	Package weight	54 g
HDMI Ethernet channel	✓	Quantity per pack *	1 pc(s)
HDCP	✓	Logistics data	
HDCP version	2.2	Master (outer) case net weight	10.8 kg
Maximum refresh rate	60 Hz	Harmonized System (HS) code	84733080
AWG wire size	30	Master (outer) case width	330 mm
Connector contacts plating *	Gold	Master (outer) case length	450 mm
Cable material	Copper	Master (outer) case height	280 mm
Cable jacket material	Polyvinyl chloride (PVC)	Master (outer) case gross weight	11.4 kg
Magnetically shielded	✓	Products per master (outer) case	200 pc(s)
Cable shielding	Aluminum mylar foil		



4719264646386



0672792008337



672792008337

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date