



Dahua Technology Lite DHI-TPC-DF1241-B2F2-DW-S8 cámara de vigilancia Torreta Cámara de seguridad IP Interior y exterior 2336 x 1752 Pixeles Techo/pared

Marca : Dahua Technology

Familia de productos: Lite

Código del producto: DHI-TPC-DF1241-B2F2-DW-S8

Nombre del producto : DHI-TPC-DF1241-B2F2-DW-S8

Dahua Technology Lite DHI-TPC-DF1241-B2F2-DW-S8. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Torreta. Iluminación mínima: 0.05 Lux, Ángulo de visión del objetivo, horizontal: 94°, Ángulo de visión del objetivo, vertical: 72°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"), Tipo de sensor (módulo térmico): Vanadium Oxide Uncooled Focal Plane Arrays. Zoom digital: 16x, Intervalo de longitud focal: 2 mm

Performance		Video	
Type *	IP security camera	Back Light Compensation (BLC)	✓
Placement supported *	Indoor & outdoor	Highlight Compensation (HLC)	✓
Connectivity technology *	Wired	Digital Wide Dynamic Range (DWDR)	✓
Wide Dynamic Range (WDR)	✓	Region of Interest (ROI) encoding	✓
Day/night mode	✓		
Design		Audio	
Form factor *	Turret	Audio input channels	1 channels
Mounting type *	Ceiling/wall	Audio output channels	1 channels
Product colour *	White	Audio formats supported	G.711 A-law, G.711 µ-law, PCM
International Protection (IP) code	IP67	Signal-to-Noise Ratio (SNR)	56 dB
Camera		Network	
Minimum illumination	0.05 lx	Ethernet LAN *	✓
Lens viewing angle, horizontal	94°	Ethernet interface type	Fast Ethernet
Lens viewing angle, vertical	72°	Supported network protocols	HTTPS; HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP
White balance	Auto, Indoor, Manual, Natural, Outdoor, Street lamp	Number of users	10 user(s)
Camera pixel size	12 µm	Storage	
Response waveband	8 - 14 µm	Card reader integrated	✓
Camera shutter speed	1/30000 - 1 s	Compatible memory cards	MicroSD (TransFlash)
Adjustment shutter speed	Auto/Manual	Maximum memory card size	256 GB
Image sensor		Ports & interfaces	
Number of sensors	1	Ethernet LAN (RJ-45) ports	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	RS-485 ports	1
Sensor type (thermal module)	Vanadium Oxide Uncooled Focal Plane Arrays	Security	
Effective sensor resolution (thermal module)	256 x 192 pixels	Alarm input channels	1
Sensor type *	CMOS	Alarm output channels	1
Lens system		Management features	
Zoom capability	✓	Web browser	✓
Digital zoom	16x	Power	
Focal length range	2 mm	Power source type *	DC, PoE
Maximum aperture number	1	Power consumption (typical)	6.5 W
Night vision		Power consumption (max)	13 W
Night vision *	✓	DC output voltage	12
Night vision distance	30 m	DC output current	1.2 A
LED type	IR		

Video		Operational conditions	
Maximum resolution *	2336 x 1752 pixels	Operating temperature (T-T)	-30 - 50 °C
Total megapixels *	4 MP	Storage temperature (T-T)	-30 - 70 °C
Video compression formats	H.264B, H.264H, H.264M, H.265	Operating relative humidity (H-H)	0 - 95%
Supported graphics resolutions	352 x 288, 640 x 480 (VGA), 704 x 576, 1024 x 768 (XGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)	Weight & dimensions	
		Height	112 mm
Frame rate	30 fps	Diameter	12.2 cm
Thermal frame rate (NTSC)	50 Hz	Weight	850 g
Thermal frame rate (PAL)	60 Hz	Packaging data	
Noise reduction	✓	Package width	155 mm
Noise reduction technology	2D noise reduction, 3D noise reduction	Package depth	155 mm
		Package height	135 mm
		Package weight	1 kg
Packaging content			
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-JAN-2025. Prints or copies of Information are only valid on the printed Publication date