

Sharp PN-ME502 pantalla de señalización Pantalla plana de señalización digital 127 cm (50") LED 450 cd / m² 4K Ultra HD Negro 18/7

Marca : Sharp

Código del producto: PN-ME502

Nombre del producto : PN-ME502

Sharp PN-ME502. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 127 cm (50"), Tecnología de visualización: LED, Resolución de la pantalla: 3840 x 2160 Píxeles, Brillo de pantalla: 450 cd / m², Tipo HD: 4K Ultra HD. Horas de funcionamiento (horas/días): 18/7. Color del producto: Negro

Display		Design	
Panel type	ADS	Product colour *	Black
LED backlight	✓	Screen shape	Flat
LED backlighting type	Direct-lit LED	VESA mounting *	✓
Display diagonal *	127 cm (50")	Panel mounting interface	400 x 400 mm
Display technology *	LED	Bezel width (bottom)	9.9 mm
Display resolution *	3840 x 2160 pixels	Bezel width (side)	9.9 mm
Display brightness *	450 cd/m ²	Bezel width (top)	9.9 mm
HD type *	4K Ultra HD	Performance	
Touchscreen *	✗	Purpose *	Commercial
Response time	8 ms	On Screen Display (OSD)	✓
Contrast ratio (typical)	4000:1	Operating hours (hours/days)	18/7
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Power consumption (typical) *	85 W
Horizontal scan range	15 - 135 kHz	Power consumption (standby) *	0.5 W
Vertical scan range	23 - 76 Hz	Power consumption (max)	105 W
Native refresh rate	60 Hz	Computer system	
Ports & interfaces		Built-in processor *	✗
HDMI ports quantity *	3	Weight & dimensions	
HDMI version	2.0	Display width	1118.6 mm
DVI port *	✗	Display depth	62 mm
USB port *	✓	Display height	639.2 mm
USB ports quantity	4	Display weight	11.7 kg
USB connector type	USB Type-A, USB Type-C	Packaging data	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Package width	1202 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Package depth	156 mm
USB Type-C DisplayPort Alternate Mode	✓	Package height	719 mm
Ethernet LAN *	✓	Package weight	17.5 kg
Ethernet LAN (RJ-45) ports	1	Packaging content	
RS-232C	✓	Remote control included	✓
Design		Batteries included	✓
Product design *	Digital signage flat panel	Cables included	AC, HDMI
Placement supported *	Indoor	Operational conditions	
Orientation	Horizontal/Vertical	Operating relative humidity (H-H)	20 - 80%
		Storage relative humidity (H-H)	10 - 80%



0805736078602



805736078602

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date