

## Dahua Technology Lite HAC-HFW1200D-0360B cámara de vigilancia Bala (forma) Cámara de seguridad CCTV Interior 1920 x 1080 Pixeles Techo/pared

Marca : Dahua Technology Familia de productos: Lite Código del producto: HAC-HFW1200D-0360B

Nombre del producto : HAC-

HFW1200D-0360B

Dahua Technology Lite HAC-HFW1200D-0360B. Tipo: Cámara de seguridad CCTV, Colocación compatible: Interior. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.02 Lux, Ángulo de campo de visión (FOV): 87.5°, Ángulo de rotación: 360°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Diámetro de lente: 3.6 mm, Intervalo de longitud focal: 6 - 8 mm

Performance		Video	
Type * Placement supported *  Design	CCTV security camera Indoor	Supported graphics resolutions Supported video modes Frame rate Analog signal format system	1920 x 1080 (HD 1080) 720p 30 fps PAL
Form factor *  Mounting type *  Product colour *  International Protection (IP) code	Bullet Ceiling/wall White IP67	Noise reduction  Noise reduction technology  Back Light Compensation (BLC)	✓ Ultra 2D noise reduction ✓
Camera  Minimum illumination Field of view (FOV) angle Angle of rotation Tilt angle range White balance Camera shutter type Camera shutter speed	0.02 lx 87.5° 360° 0 - 87° Auto, Manual Electronic 1/25 ~ 1 / 100000 s	Highlight Compensation (HLC) Digital Wide Dynamic Range (DWDR)	<b>*</b>
		Ports & interfaces  BNC output ports  Power	1
		Power source type * Power consumption (typical)	DC 5.4 W
		• • • • • • • • • • • • • • • • • • • •	
Image sensor		DC output voltage	12
Image sensor Number of sensors Optical sensor size Sensor type *	1 25.4 / 2.7 mm (1 / 2.7") CMOS	DC output voltage  Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)	12 -40 - 60 °C -40 - 60 °C
Number of sensors Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	DC output voltage  Operational conditions  Operating temperature (T-T)	12 -40 - 60 °C
Number of sensors Optical sensor size Sensor type * Lens system	25.4 / 2.7 mm (1 / 2.7") CMOS	DC output voltage  Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)	-40 - 60 °C -40 - 60 °C 0 - 95%
Number of sensors Optical sensor size Sensor type *  Lens system Lens diameter Focal length range Minimum aperture number  Night vision Night vision *	25.4 / 2.7 mm (1 / 2.7") CMOS  3.6 mm 6 - 8 mm 1.85	DC output voltage  Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)  Storage relative humidity (H-H)	-40 - 60 °C -40 - 60 °C 0 - 95%
Number of sensors Optical sensor size Sensor type * Lens system Lens diameter Focal length range Minimum aperture number Night vision	25.4 / 2.7 mm (1 / 2.7") CMOS 3.6 mm 6 - 8 mm 1.85	DC output voltage  Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)  Storage relative humidity (H-H)  Weight & dimensions  Width  Depth  Height	12  -40 - 60 °C  -40 - 60 °C  0 - 95%  0 - 95%  241.8 mm  90.4 mm  90.4 mm
Number of sensors Optical sensor size Sensor type *  Lens system Lens diameter Focal length range Minimum aperture number  Night vision  Night vision * LED type	25.4 / 2.7 mm (1 / 2.7") CMOS  3.6 mm 6 - 8 mm 1.85	DC output voltage  Operational conditions  Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)  Weight & dimensions  Width Depth Height Weight	12  -40 - 60 °C  -40 - 60 °C  0 - 95%  0 - 95%  241.8 mm  90.4 mm  90.4 mm
Number of sensors Optical sensor size Sensor type *  Lens system Lens diameter Focal length range Minimum aperture number  Night vision Night vision * LED type Number of illumination LEDs	25.4 / 2.7 mm (1 / 2.7") CMOS  3.6 mm 6 - 8 mm 1.85	DC output voltage  Operational conditions  Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)  Weight & dimensions  Width Depth Height Weight  Packaging data	12 -40 - 60 °C -40 - 60 °C 0 - 95% 0 - 95%  241.8 mm 90.4 mm 90.4 mm 590 g



6939554955143

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.