

Dahua Technology Cooper DH-HAC-B1A51N-U-0280B cámara de vigilancia Bala (forma) Cámara de seguridad CCTV Exterior 2880 x 1620 Pixeles Techo/pared/Tubo

Marca : Dahua Technology Familia de productos: Cooper Código del producto: DH-HAC-B1A51N-U-0280B

Nombre del producto : DH-HAC-B1A51N-U-0280B

Dahua Technology Cooper DH-HAC-B1A51N-U-0280B. Tipo: Cámara de seguridad CCTV, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 106°, Ángulo de visión del objetivo, vertical: 56°. Tipo de sensor: CMOS. Distancia de detección: 66 m, Distancia de observación: 26.4 m, Distancia de reconocimiento: 13.2 m

Performance		Video		
Type *	CCTV security camera	Total megapixels * 5 MP		
Placement supported * Connectivity technology * Day/night mode	Outdoor Wired	Supported graphics resolutions	960 x 480, 960 x 576, 1920 x 1080 (HD 1080), 2560 x 1440, 2880 x 1620	
Day/Hight Hiode	CE-LVD: EN 62368-1; CE-EMC: EN	Frame rate	30 fps	
Certification	55032; EN 55035	Analog signal format system	NTSC	
Design		Noise reduction	✓	
Form factor * Mounting type * Product colour *	Bullet Ceiling/Wall/Pole White Plastic IP67	Noise reduction technology Gain control type	2D noise reduction Auto/Manual	
		Back Light Compensation (BLC)	Auto/Mariuar ✓	
		•		
Housing material		Highlight Compensation (HLC)	✓	
International Protection (IP) code		Digital Wide Dynamic Range (DWDR)	✓	
Camera		Smart IR	✓	
Minimum illumination Angle of rotation Lens viewing angle, horizontal Lens viewing angle, vertical	0 lx 360° 106° 56° 125°	Audio		
		Signal-to-Noise Ratio (SNR)	65 dB	
		Network		
Lens viewing angle, diagonal		Ethernet LAN *	×	
Tilt angle range	0 - 90°	Wi-Fi *	×	
Pan range White balance Camera shutter type Camera shutter speed Number of Privacy masking areas	0 - 360° Area white balance, Auto Electronic 1/30 - 1/100000 s 8	Bluetooth *	×	
		Storage		
		Built-in HDD *	X	
			^	
Image sensor		Security		
Progressive scan	✓	Mirror	/	
Sensor type *	CMOS	Power		
Lens system		Power source type *	DC	
•	66 m	Power consumption (max)	3.7 W	
Detect distance Observe distance	26.4 m	DC output voltage	12	
Recognize distance	13.2 m	Operational conditions		
Identify distance	6.6 m	Operating temperature (T-T)	-40 - 60 °C	
Fixed focal length	2.8 mm	Storage temperature (T-T)	-40 - 60 °C	
Closest focusing distance	1 m	Operating relative humidity (H-H)	0 - 95%	
Night vision		Storage relative humidity (H-H)	0 - 95%	
Night vision *	√ 30 m IR	Weight & dimensions		
Night vision distance		Width	146.1 mm	
LED type		Depth	70 mm	
Number of illumination LEDs	3	Height	69.8 mm	
		Weight	170 g	

Video		Packaging data		
Maximum resolution *	2880 x 1620 pixels	Package weight	250 g	
		Packaging content		
		Number of cameras *	1	

