

Dahua Technology DH-HAC-B2A51N-U-0280B-S2 cámara de vigilancia Bala (forma) Cámara de seguridad CCTV Exterior 2880 x 1620 Pixeles Techo/pared/Tubo

Marca : Dahua Technology

Código del producto: DH-HAC-B2A51NU-0280B-S2

Nombre del producto: DH-HAC-B2A51N-U-0280B-

S2

Dahua Technology DH-HAC-B2A51N-U-0280B-S2. Tipo: Cámara de seguridad CCTV, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 106°, Ángulo de visión del objetivo, vertical: 56°. Tipo de sensor: CMOS. Distancia de detección: 66 m, Distancia de observación: 26.4 m, Distancia de reconocimiento: 13.2 m

Performance		Video	
	CCTV security camera		5 MP
Type * Placement supported * Connectivity technology *	Outdoor Wired	Total megapixels * Supported graphics resolutions	960 x 480, 960 x 576, 1920 x 1080 (HD 1080), 2560 x 1440, 2880 x 1620
Day/night mode	CE-LVD: EN 62368-1; CE-EMC: EN	Frame rate Analog signal format system	30 fps NTSC
Certification	55032; EN 55035	Noise reduction	N13C ✓
Design		Noise reduction technology	2D noise reduction
Form factor * Mounting type * Product colour * Housing material International Protection (IP) code	Bullet Ceiling/Wall/Pole White Metal IP67	Gain control type	Auto/Manual
		Back Light Compensation (BLC)	✓
		Highlight Compensation (HLC)	✓
		Digital Wide Dynamic Range (DWDR)	1
Camera		Smart IR	✓
Minimum illumination Angle of rotation Lens viewing angle, horizontal Lens viewing angle, vertical Lens viewing angle, diagonal	0 lx 360° 106° 56° 125°	Audio	
		Signal-to-Noise Ratio (SNR)	65 dB
		Network	
		Ethernet LAN *	x
Tilt angle range	0 - 90°	Wi-Fi *	×
Pan range	0 - 360°	Bluetooth *	x
White balance Camera shutter type	Area white balance, Auto Electronic	Storage	
Camera shutter speed	1/30 - 1/100000 s	Built-in HDD *	x
Number of Privacy masking areas	8	Security	
Image sensor		Mirror	✓
Progressive scan	✓	Power	
Sensor type *	CMOS	Power source type *	DC
Lens system		Power consumption (max)	3.7 W
Detect distance	66 m	DC output voltage	12
Observe distance	26.4 m	Operational conditions	
Recognize distance Identify distance	13.2 m 6.6 m	Operating temperature (T-T)	-40 - 60 °C
Fixed focal length	2.8 mm	Storage temperature (T-T)	-40 - 60 °C
Closest focusing distance	1 m	Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 95% 0 - 95%
Night vision		Weight & dimensions	3 33/0
Night vision *	√ 30 m	Width	150 mm
Night vision distance		Depth	69.7 mm
LED type	IR -	Height	70 mm
Number of illumination LEDs	3	Weight	310 g

Video		Packaging data		
Maximum resolution *	2880 x 1620 pixels	Package weight	380 g	
		Packaging content		
		Number of cameras *	1	

