



## LG BU60RG video proyector Proyector de alcance estándar 6000 lúmenes ANSI DLP UHD 4K (3840x2160) Blanco

Marca : LG

Código del producto: BU60RG

Nombre del producto : BU60RG

ProBeam 4K (3840x2160) Proyector Láser con 6000 ANSI lúmenes de iluminación

LG BU60RG. Brillo de proyector: 6000 lúmenes ANSI, Tecnología de proyección: DLP, Resolución original del proyector: UHD 4K (3840x2160). Tipo de fuente de luz: Laser, Vida útil de la fuente de luz: 20000 h. Enfoque: Manual, Relación de alcance: 1.30 - 2.08, Rango de cambio Horizontal de la lente: -20 - 20%. Tipo de serie de interfaz: RS-232C. Nivel de ruido: 33 Db, Sistema operativo instalado: webOS



Projector		Features	
Supported aspect ratios	4:3, 16:10, 16:6, 16:9, 21:9	Interactive *	✗
Smart projector *	✗	Noise level *	33 dB
Screen size compatibility *	1016 - 7620 mm (40 - 300")	Operating system installed	webOS
Projector brightness *	6000 ANSI lumens	Operating system version	6.0
Projection technology *	DLP	Multimedia	
Projector native resolution *	UHD 4K (3840x2160)	Built-in speaker(s) *	✓
Contrast ratio (typical) *	3000000:1	RMS rated power	10 W
Native aspect ratio *	16:9	Number of built-in speakers	2
Light source		Design	
Light source type *	Laser	Market positioning *	Presentation
Service life of light source *	20000 h	Product type *	Standard throw projector
Lens system		Product colour *	White
Focus *	Manual	Cable lock slot	✓
Zoom capability	✓	Cable lock slot type	Kensington
Throw ratio	1.30 - 2.08	Display	
Horizontal lens shift range	-20 - 20%	Built-in display *	✗
Vertical lens shift range	-50 - 50%	Power	
Offset	100%	Power source *	AC
Video		Power consumption (typical) *	440 W
Full HD *	✓	Power consumption (standby) *	0.5 W
Ports & interfaces		AC input frequency	50 - 60 Hz
HDMI version	2.0	AC adapter output voltage	100 - 240 V
USB 2.0 ports quantity	2	Operational conditions	
Serial interface type *	RS-232C	Operating temperature (T-T)	0 - 40 °C
HDMI ports quantity *	2	Weight & dimensions	
DVI port *	✗	Width	370 mm
Network		Depth	290 mm
Smart TV *	✗	Height	155.7 mm
Ethernet LAN *	✓	Package width	580 mm
Ethernet LAN (RJ-45) ports	1	Package depth	441 mm
Wi-Fi *	✓	Package height	273 mm
Bluetooth	✓		

Storage		Packaging content	
Card reader integrated *	✗	Remote control included *	✓
		Cables included	AC, Serial
		Manual	✓



0195174067949



195174067949

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date