



TP-Link VIGI C350(2.8MM) cámara de vigilancia Bala (forma) Cámara de seguridad IP Exterior 2880 x 1620 Píxeles Techo

Marca : TP-Link

Familia de productos: VIGI

Código del producto: VIGI
C350(2.8MM)

Nombre del producto : VIGI
C350(2.8MM)

Cámara IP VIGI tipo bullet Full Color para exteriores de 5MP

TP-Link VIGI C350(2.8MM). Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Negro, Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.005 Lux, Ángulo de visión del objetivo, horizontal: 90°, Ángulo de visión del objetivo, vertical: 48°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Distancia de detección: 80 m, Distancia de observación: 33 m, Distancia de reconocimiento: 16 m



Performance		Audio	
Type *	IP security camera	Built-in speaker(s)	✓
Placement supported *	Outdoor	Audio system	2-way
Connectivity technology *	Wired	Audio input channels	1 channels
Day/night mode	✓	Audio output channels	1 channels
Infrared (IR) cut-off filter	✓	Sample rate	8 kHz
Built-in light	✓	Signal-to-Noise Ratio (SNR)	52 dB
Design		Built-in microphone	✓
Form factor *	Bullet	Bit rate range	0 - 64 Kbit/s
Mounting type *	Ceiling	Network	
Product colour *	Black, White	Ethernet LAN *	✓
LED indicators	✓	Networking standards	IEEE 802.3af, IEEE 802.3at
Housing material	Plastic	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS
International Protection (IP) code	IP67	Wi-Fi *	✗
Camera		Bluetooth *	✗
Minimum illumination	0.005 lx	Live view	✓
Lens viewing angle, horizontal	90°	Number of simultaneous live view channels	3 channels
Lens viewing angle, vertical	48°	Storage	
Lens viewing angle, diagonal	107°	Built-in HDD *	✗
Tilt angle range	0 - 90°	Card reader integrated	✓
Pan range	0 - 360°	Compatible memory cards	MicroSD (TransFlash)
Camera shutter speed	1/3 - 1/10000 s	Maximum memory card size	256 GB
Number of Privacy masking areas	4	Ports & interfaces	
Image sensor		Ethernet LAN (RJ-45) ports	1
Number of sensors	1	DC-in jack	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")		
Progressive scan	✓		
Sensor type *	CMOS		

Lens system		Security	
Number of lenses *	1	Password protection	✓
Detect distance	80 m	Video motion detection	✓
Observe distance	33 m	IP address filtering	✓
Recognize distance	16 m	HTTPS encryption	✓
Maximum aperture number	1.6	Intelligent Video Surveillance (IVS) system features	Vehicle detection
Identify distance	8 m	Human and vehicle targets classification	✓
Fixed focal length	2.8 mm	Digest authentication	✓
Night vision		Management features	
Night vision *	✓	Web browser	✓
Night vision distance	30 m	Reset button	✓
LED type	IR	Behavior analysis	Intrusion detection, Line crossing detection, Object removal detection, Region exiting detection
Number of illumination LEDs	4	Power	
Infra-red wavelength	850 nm	Power source type *	DC, PoE
Video		Power consumption (max)	9 W
Maximum resolution *	2880 x 1620 pixels	Power consumption (Power over Ethernet (PoE))	10.5 W
Total megapixels *	5 MP	DC output voltage	12
Video compression formats	H.264, H.264+, H.265, H.265+	Operational conditions	
Supported graphics resolutions	320 x 240, 352 x 288, 640 x 480 (VGA), 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2688 x 1520, 2880 x 1620	Operating temperature (T-T)	-30 - 60 °C
Frame rate	30 fps	Storage temperature (T-T)	-40 - 60 °C
Video streaming	✓	Operating relative humidity (H-H)	0 - 95%
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness	Storage relative humidity (H-H)	0 - 95%
Privacy masking	✓	Weight & dimensions	
Bit rate control	Constant Bit Rate (CBR), Variable Bit Rate (VBR)	Width	186.9 mm
Bit rate	256 Kbps - 6 Mbps	Height	71.5 mm
Back Light Compensation (BLC)	✓	Length	78.4 mm
Highlight Compensation (HLC)	✓	Packaging data	
Digital Wide Dynamic Range (DWDR)	✓	Package type	Box
Region of Interest (ROI) encoding	✓	Sustainability	
Smart IR	✓	Sustainability compliance	✓
		Compliance certificates	BSMI, CE, Federal Communications Commission (FCC), KC, VCCI
		Packaging content	
		Number of cameras *	1



4895252502992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date