

Lenovo ThinkSystem SR250 V3 servidor Bastidor (1U) Intel Xeon E E-2468 2.6 GHz 32 GB DDR5-SDRAM 800 W



Marca: Lenovo

Familia de productos: ThinkSystem Código del producto: 7DCLA01TLA

Nombre del producto: SR250

V3

Lenovo ThinkSystem SR250 V3. Familia de procesador: Intel Xeon E, Frecuencia del procesador: 2.6 GHz, Modelo del procesador: E-2468. Memoria interna: 32 GB, Tipo de memoria interna: DDR5-SDRAM, Diseño de memoria (ranuras x tamaño): 1 x 32 GB. Ethernet, Tecnología de cableado: 10/100/1000Base-T(X). Fuente de alimentación: 800 W, Suministro de energía redundante (RPS), soporte. Tipo de chasis: Bastidor (1U)

Dunganan		Doube C intenfere	
Processor		Ports & interfaces	
Processor family * Processor model *	Intel Intel Xeon E E-2468 2.6 GHz	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity VGA (D-Sub) ports quantity Serial ports quantity	3 1 1
Processor boost frequency	5.2 GHz	Design	
Performance cores Processor cores Processor cache	8 8 24 MB	Chassis type * Product colour	Rack (1U) Black, Silver
Motherboard chipset	Intel C266	Performance	
Number of processors installed	1	Performance management	XClarity Controller Platinum
Memory		Trusted Platform Module (TPM)	✓
Internal memory *	32 GB	Trusted Platform Module (TPM) version	2.0
Internal memory type * Memory slots	DDR5-SDRAM 4x DIMM	Software	
ECC Memory clock speed 4800 MHz	✓	Compatible operating systems *	Microsoft Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Memory layout (slots x size)	1 x 32 GB	Power	
Maximum internal memory * Storage	128 GB	Redundant power supply (RPS) support *	✓
RAID support *	√	Power supply *	800 W
RAID levels	0, 1, 5, 10	Number of redundant power supplies supported	2
Supported RAID controllers	5350-8i	Power supply input voltage	100 - 240 V
Internal drive bays	8	Power supply input frequency	50/60 Hz
Supported storage drive interfaces	SAS, Serial ATA	Operational conditions	
Graphics		Operating temperature (T-T)	5 - 45 °C
On-board graphics card	✓	Storage temperature (T-T)	-40 - 60 °C
Maximum graphics card memory	16 MB	Operating relative humidity (H-H)	8 - 90%
Network		Storage relative humidity (H-H)	8 - 90%
LAN controller	Broadcom BCM5720	Operating altitude	0 - 3050 m
Ethernet LAN	✓	Weight & dimensions	
Cabling technology	10/100/1000Base-T(X)	Width	434.4 mm
Ethernet interface type	Gigabit Ethernet	Depth	561 mm 43 mm
Ports & interfaces		Height	43
Ethernet LAN (RJ-45) ports *	2	Technical details	
USB 2.0 ports quantity	1	Supported storage drives form factor (rear)	2.5"

