



# Lenovo ThinkSystem SR650 V3 servidor Bastidor (2U) Intel® Xeon Silver 4514Y 2 GHz 32 GB DDR5-SDRAM 750 W



Marca : Lenovo

Familia de productos:  
ThinkSystem

Código del producto:  
7D76A07CLA

Nombre del producto : SR650  
V3

Lenovo ThinkSystem SR650 V3. Familia de procesador: Intel® Xeon Silver, Frecuencia del procesador: 2 GHz, Modelo del procesador: 4514Y. Memoria interna: 32 GB, Tipo de memoria interna: DDR5-SDRAM, Diseño de memoria (ranuras x tamaño): 1 x 32 GB. Fuente de alimentación: 750 W, Suministro de energía redundante (RPS), soporte. Tipo de chasis: Bastidor (2U)

Processor		Ports & interfaces	
Processor manufacturer *	Intel	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Processor family *	Intel Xeon Silver	VGA (D-Sub) ports quantity	1
Processor model *	4514Y	<b>Design</b>	
Processor frequency *	2 GHz	Chassis type *	Rack (2U)
Processor boost frequency	3.4 GHz	Product colour	Black, Metallic
Processor cores	16	<b>Performance</b>	
Processor cache	30 MB	Performance management	XClarity Controller Platinum
Number of processors installed	1	Trusted Platform Module (TPM)	✓
Maximum number of SMP processors	2	Trusted Platform Module (TPM) version	2.0
<b>Memory</b>		<b>Software</b>	
Internal memory *	32 GB	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server
Internal memory type *	DDR5-SDRAM	<b>Power</b>	
Memory slots	32x DIMM	Redundant power supply (RPS) support *	✓
ECC	✓	Power supply *	750 W
Memory clock speed	4800 MHz	Number of redundant power supplies supported	2
Memory layout (slots x size)	1 x 32 GB	Power supply input frequency	50 - 60 Hz
Maximum internal memory *	8.19 TB	<b>Operational conditions</b>	
<b>Storage</b>		Operating temperature (T-T)	5 - 45 °C
RAID support *	✓	Storage temperature (T-T)	-40 - 60 °C
RAID levels	0, 1, 5, 6, 10, 50, 60	Operating relative humidity (H-H)	8 - 90%
Supported RAID controllers	9350-8i	Storage relative humidity (H-H)	8 - 90%
Hot-swap	✓	Operating altitude	0 - 3050 m
Optical drive type *	✗	<b>Weight &amp; dimensions</b>	
Internal drive bays	8	Width	445 mm
Supported storage drive interfaces	SAS	Depth	766 mm
<b>Graphics</b>		Height	87 mm
On-board graphics card	✓	<b>Technical details</b>	
Maximum graphics card memory	16 MB	2.5" HDD support	8
<b>Ports &amp; interfaces</b>			
Ethernet LAN (RJ-45) ports *	1		
USB 2.0 ports quantity	2		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-DEC-2024. Prints or copies of Information are only valid on the printed Publication date