



## Dahua Technology PFS4218-16ET-190 Gestionado L2 Fast Ethernet (10/100) Energía sobre Ethernet (PoE) 1U Negro

**Marca :** Dahua Technology

**Código del producto:** DH-PFS4218-16ET-190

**Nombre del producto :** PFS4218-16ET-190

Dahua Technology PFS4218-16ET-190. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 16. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 4000 entradas, Capacidad de conmutación: 8.8 Gbit/s. Estándares de red: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE.... Energía sobre Ethernet (PoE). Montaje en rack, Factor de forma: 1U

Management features		Data transmission	
Switch type *	Managed	MAC address table *	4000 entries
Switch layer	L2	<b>Security</b>	
Quality of Service (QoS) support	✓	DHCP features	DHCP client
Web-based management	✓	IP-MAC-Port binding	✓
System event log	✓	Authentication	Port-based authentication
<b>Ports &amp; interfaces</b>		Authentication type	IEEE 802.1x
Basic switching RJ-45 Ethernet ports quantity *	16	<b>Protocols</b>	
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	Management protocols	SNMP V1/V2C/V3
Fast Ethernet (copper) ports quantity	16	<b>Design</b>	
Combo SFP ports quantity	2	Rack mounting *	✓
<b>Network</b>		Form factor	1U
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Product colour	Black
		LED indicators	✓
10G support *	✗	<b>Power</b>	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	AC input voltage	100 - 240 V
Port mirroring	✓	<b>Power over Ethernet (PoE)</b>	
Full duplex	✓	Power over Ethernet (PoE) *	✓
Flow control support	✓	Power over Ethernet (PoE) ports quantity	16
Link aggregation	✓	Total Power over Ethernet (PoE) budget	190 W
<b>Optical fiber</b>		<b>Operational conditions</b>	
Fiber ethernet cabling technology	1000BASE-X	Operating temperature (T-T)	-10 - 55 °C
<b>Data transmission</b>		Operating relative humidity (H-H)	10 - 90%
Switching capacity *	8.8 Gbit/s	<b>Weight &amp; dimensions</b>	
Forwarding rate	5.36 Mpps	Width	440 mm
		Depth	300 mm
		Height	44 mm
		Weight	3.51 kg



6939554912825

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date