

## Dahua Technology N3 router inalámbrico Ethernet Banda única (2,4 GHz) Negro

Marca: Dahua Technology Código del producto: DH-N3

Nombre del producto: N3

Dahua Technology N3. Tipo de conexión WAN: RJ-45. Banda Wi-Fi: Banda única (2,4 GHz), Máximo estándar Wi-Fi: Wi-Fi 4 (802.11n), Tasa de transferencia de datos WLAN (máx.): 300 Mbit/s. Tipo de interfaz Ethernet LAN: Ethernet, Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s, Tecnología de cableado: 10/100/1000Base-T(X). Algoritmos de seguridad: WPA-PSK, WPA2-PSK. Tipo de producto: Router de mesa, Color del producto: Negro





WAN connection		Protocols	
Ethernet WAN *	✓	Universal Plug and Play (UPnP)	✓
DSL WAN *	×	Design	
SIM card slot *	×	Product colour	Black
3G/4G USB modem compatibility *	×	Indication light	✓
WAN connection type	RJ-45	Product type *	Tabletop router
Wireless LAN features		Packaging content	
Top Wi-Fi standard * WLAN data transfer rate (max) *	Single-band (2.4 GHz) Wi-Fi 4 (802.11n) 300 Mbit/s 802.11b, 802.11q, Wi-Fi 4 (802.11n)	Cables included AC adapter included Manual	LAN (RJ-45) ✓
WLAN data transfer rate (first band)	•	Antenna	
Channels quantity Channel bandwidth	13 channels 40 MHz	Antenna design * Antenna gain level (max)	External 3 dBi
Network		Antennas quantity	2
Ethernet LAN *	<b>✓</b>	Antenna direction type	Omni-directional
Ethernet LAN interface type *	Ethernet	Features	
Ethernet LAN data rates	10,100,1000 Mbit/s	Firmware upgradeable	✓
Cabling technology	10/100/1000Base-T(X)	Power	
Port forwarding Automatic channel selection	1	Power source type * Output voltage	DC 12 V
Ports & interfaces		Output current	0.5 A
Ethernet LAN (RJ-45) ports *	4	Power consumption (typical)	3.2 W
USB port *	×	External power adapter	✓
DC-in jack	✓	Operational conditions	
Management features		Operating temperature (T-T)	-10 - 40 °C
Web-based management	✓	Storage temperature (T-T)	-20 - 70 °C

Management features		Operational conditions	
Quality of Service (QoS) support	✓	Operating relative humidity (H-H)	10 - 90%
WPS push button	✓	Weight & dimensions	
Security		Width	121 mm
Security algorithms	WPA-PSK, WPA2-PSK	Depth	172 mm
DMZ support	<b>✓</b>	Height	33 mm
		Weight	125 g
Protocols		Packaging data	
DHCP client	<b>✓</b>	Package width	245 mm
DHCP server	•	Package depth	218 mm
		Package height	45 mm
		Package weight	303 g
		Number of products included	1 pc(s)
		Other features	
		Frequency range	2.412 - 2.484 GHz



6923172560100

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.