## Lenovo ThinkPad T14 Intel Core Ultra 5 125U Computadora portátil 35.6 cm (14") WUXGA 16 GB DDR5-SDRAM 512 GB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Español Negro

Marca : Lenovo Familia de productos: Código del producto: ThinkPad 21MMS2PC00

## Nombre del producto: T14

- Windows 11 Pro 64-bit
- Intel Core Ultra 5 125U (12MB Cache)
- 35.6 cm (14") WUXGA 1920 x 1200 IPS
- 16GB (5600MHz) DDR5-SDRAM & 512GB SSD

Intel Core Ultra 5 125U (12MB Cache), 16GB DDR5-SDRAM, 512GB SSD, 35.6 cm (14") WUXGA 1920 x 1200 IPS, Intel Graphics, LAN, WLAN, Webcam, Windows 11 Pro 64-bit

Lenovo ThinkPad T14. Tipo de producto: Computadora portátil, Factor de forma: Concha. Familia de procesador: Intel Core Ultra 5, Modelo del procesador: 125U. Diagonal de la pantalla: 35.6 cm (14"), Tipo HD: WUXGA, Resolución de la pantalla: 1920 x 1200 Pixeles. Memoria interna: 16 GB, Tipo de memoria interna: DDR5-SDRAM. Capacidad total de almacenaje: 512 GB, Unidad de almacenamiento: SSD. Modelo de gráficos en tarjeta: Intel Graphics. Sistema operativo instalado: Windows 11 Pro. Color del producto: Negro. Peso: 1.38 kg





Design		Audio	
Product type * Product colour * Form factor * Housing material	Laptop Black Clamshell Carbon fibre, Polycarbonate (PC)	Audio system  Number of built-in speakers  Speaker power  Camera	Dolby Audio 2 2 W
Display		Front camera	<b>✓</b>
Display diagonal *       35.6 cm (14")         Display resolution *       1920 x 1200 pixels         Fouchscreen *       X         HD type       WUXGA	Front camera resolution (numeric) Infrared (IR) camera Privacy camera Privacy type	5 MP	
Panel type	IPS	Network	
LED backlight Native aspect ratio Anti-glare screen Display brightness Maximum refresh rate Contrast ratio (typical)	✓ 16:10 ✓ 400 cd/m² 60 Hz 1000:1	Top Wi-Fi standard * Wi-Fi standards Mobile network connection * Antenna type WLAN controller model	Wi-Fi 6E (802.11ax) Wi-Fi 6E (802.11ax)  x 2x2 Intel Wi-Fi 6E AX211
Processor		WLAN controller manufacturer Ethernet LAN	Intel  ✓
Processor manufacturer * Processor family * Processor generation Processor model * Processor cores	Intel Intel Core Ultra 5 Intel® Core™ Ultra (Series 1) 125U 12	Ethernet LAN data rates Bluetooth Bluetooth version WWAN	100,1000 Mbit/s  5.3  Not installed
Processor threads	14	Ports & interfaces	
Processor boost frequency Performance cores Efficient cores Low Power Efficient-cores	4.3 GHz 2 8 2	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports HDMI ports quantity * HDMI version	2 1 1 2.1

•		D. J. C. L. C.	
Processor		Ports & interfaces	
Performance-core Max Turbo Frequency	4.3 GHz	Thunderbolt 4 ports quantity	2
Efficient-core Max Turbo Frequency	3.6 GHz	Intel® Thunderbolt 4	<b>/</b>
Low Power Efficient-core Max Turbo Frequency	2.1 GHz	Combo headphone/mic port  USB Type-C DisplayPort Alternate	✓ ✓
Performance-core base frequency	1.3 GHz	Mode	
Efficient-core base frequency	0.8 GHz	USB Sleep-and-Charge USB Sleep-and-Charge ports	1
Low Power Efficient-core Base Frequency	700 MHz		1
Processor cache	12 MB	Performance	
Processor cache type	Smart Cache	Motherboard chipset	Intel SoC
Processor base power	15 W	Keyboard	
Maximum turbo power	57 W	Pointing device	ThinkPad UltraNav
Neural processor unit (NPU)		Numeric keypad *	×
Neural processor unit (NPU)	Intel Al Boost	Keyboard backlit	•
Maximum frequency NPU	1.4 GHz	Spill-resistant keyboard	Coorde
Sparsity support	<b>✓</b>	Keyboard language	Spanish
Windows Studio effects support	✓	Software	
Al datatype support on NPU	FP16, FP32, Int8	Operating system architecture	64-bit
Al software frameworks supported by NPU	DirectML, ONNX RT, OpenVINO, Windows ML	Operating system language	Spanish
Memory		Operating system installed *	Windows 11 Pro
Internal memory *	16 GB	Battery	
Internal memory type	DDR5-SDRAM	Battery technology	Lithium Polymer (LiPo)
Memory clock speed	5600 MHz	Number of battery cells  Battery capacity *	4 52.5 Wh
Memory form factor	SO-DIMM	Fast charging	✓
Memory slots	2x SO-DIMM	r asc charging	•
		<b>a</b>	
Maximum internal memory *	64 GB	Power	
Memory channels	64 GB Dual-channel	Power USB Power Delivery (USB PD)	<b>✓</b>
Memory channels  Storage	Dual-channel		•
Memory channels  Storage  Total storage capacity *	Dual-channel 512 GB	USB Power Delivery (USB PD)	*
Memory channels  Storage  Total storage capacity * Storage media *	Dual-channel 512 GB SSD	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type	
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity	Dual-channel 512 GB	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)	✓
Memory channels  Storage  Total storage capacity * Storage media *	Dual-channel  512 GB SSD 512 GB	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM)	✓ Kensington
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed	Dual-channel  512 GB SSD 512 GB 1	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM)  version	✓ Kensington
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity	Dual-channel  512 GB  SSD  512 GB  1  512 GB	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM)	✓ Kensington ✓ 2.0
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM) version  Password protection  Password protection type	✓ Kensington ✓ 2.0
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor	Dual-channel  512 GB  SSD  512 GB  1  512 GB  TLC  PCI Express 4.0  M.2	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM) version  Password protection  Password protection type  Operational conditions	Kensington  2.0  BIOS, Power on, SSD, Supervisor
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type *	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  M.2  X	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM) version  Password protection  Password protection type	✓ Kensington ✓ 2.0
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated	Dual-channel  512 GB  SSD  512 GB  1  512 GB  TLC  PCI Express 4.0  M.2	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM)  version  Password protection  Password protection type  Operational conditions  Operating temperature (T-T)	Kensington  2.0  BIOS, Power on, SSD, Supervisor  5 - 35 °C
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  M.2  X	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM)  version  Password protection  Password protection type  Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)	Kensington  2.0  BIOS, Power on, SSD, Supervisor  5 - 35 °C  5 - 43 °C  8 - 95%  5 - 95%
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics Discrete graphics card model *	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  M.2  X  Not available	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions  Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	Kensington  2.0  BIOS, Power on, SSD, Supervisor  5 - 35 °C  5 - 43 °C  8 - 95%
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board graphics card *	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  M.2  X  Not available	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM)  version  Password protection  Password protection type  Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)	Kensington  2.0  BIOS, Power on, SSD, Supervisor  5 - 35 °C  5 - 43 °C  8 - 95%  5 - 95%
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board GPU manufacturer	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  M.2  X  Not available  Intel	USB Power Delivery (USB PD)  Security  Cable lock slot  Cable lock slot type  Trusted Platform Module (TPM)  Trusted Platform Module (TPM)  version  Password protection  Password protection type  Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)  Storage relative humidity (H-H)  Maximum shipping altitude	Kensington  2.0  BIOS, Power on, SSD, Supervisor  5 - 35 °C  5 - 43 °C  8 - 95%  5 - 95%  3048 m  RoHS
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board GPU manufacturer Discrete graphics card *	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  ✓ M.2  ×  X  Not available  ✓ Intel  X	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude  Certificates Compliance certificates	<ul> <li>Kensington</li> <li>2.0</li> <li>BIOS, Power on, SSD, Supervisor</li> <li>5 - 35 °C</li> <li>5 - 43 °C</li> <li>8 - 95%</li> <li>5 - 95%</li> <li>3048 m</li> </ul> RoHS ENERGY STAR® 8.0 EPEAT™ Gold
Storage Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics Discrete graphics card model * On-board GPU manufacturer Discrete graphics card family	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0   M.2   X  Not available  Intel X Intel Graphics	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude  Certificates	<ul> <li>Kensington</li> <li>Z.0</li> <li>BIOS, Power on, SSD, Supervisor</li> <li>5 - 35 °C</li> <li>5 - 43 °C</li> <li>8 - 95%</li> <li>5 - 95%</li> <li>3048 m</li> <li>RoHS</li> <li>ENERGY STAR® 8.0 EPEAT™ Gold Registered[3] ErP Lot 6/26 RoHS compliant TCO Certified 9.0 MIL-</li> </ul>
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model *	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  ✓ M.2  ×  X  Not available  ✓ Intel  X	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude  Certificates Compliance certificates	<ul> <li>Kensington</li> <li>2.0</li> <li>BIOS, Power on, SSD, Supervisor</li> <li>5 - 35 °C</li> <li>5 - 43 °C</li> <li>8 - 95%</li> <li>5 - 95%</li> <li>3048 m</li> </ul> RoHS ENERGY STAR® 8.0 EPEAT™ Gold Registered[3] ErP Lot 6/26 RoHS
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model * Audio	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  ✓ M.2  ×  X  Not available  ✓ Intel X Intel Graphics Intel Graphics	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude  Certificates Compliance certificates	<ul> <li>Kensington</li> <li>Z.0</li> <li>BIOS, Power on, SSD, Supervisor</li> <li>5 - 35 °C</li> <li>5 - 43 °C</li> <li>8 - 95%</li> <li>5 - 95%</li> <li>3048 m</li> <li>RoHS</li> <li>ENERGY STAR® 8.0 EPEAT™ Gold Registered[3] ErP Lot 6/26 RoHS compliant TCO Certified 9.0 MIL-</li> </ul>
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model *	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0   M.2   X  Not available  Intel X Intel Graphics	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude  Certificates Compliance certificates  Certification  Weight & dimensions Width	<ul> <li>Kensington</li> <li>✓</li> <li>2.0</li> <li>✓</li> <li>BIOS, Power on, SSD, Supervisor</li> <li>5 - 35 °C</li> <li>5 - 43 °C</li> <li>8 - 95%</li> <li>5 - 95%</li> <li>3048 m</li> <li>RoHS</li> <li>ENERGY STAR® 8.0 EPEAT™ Gold Registered[3] ErP Lot 6/26 RoHS compliant TCO Certified 9.0 MIL-STD-810H</li> <li>315.9 mm</li> </ul>
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model * Audio	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  ✓ M.2  ×  X  Not available  ✓ Intel X Intel Graphics Intel Graphics	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude  Certificates Compliance certificates  Certification  Weight & dimensions Width Depth	<ul> <li>Kensington</li> <li>2.0</li> <li>BIOS, Power on, SSD, Supervisor</li> <li>5 - 35 °C</li> <li>5 - 43 °C</li> <li>8 - 95%</li> <li>5 - 95%</li> <li>3048 m</li> <li>RoHS</li> <li>ENERGY STAR® 8.0 EPEAT™ Gold Registered[3] ErP Lot 6/26 RoHS compliant TCO Certified 9.0 MIL-STD-810H</li> <li>315.9 mm</li> <li>223.7 mm</li> </ul>
Memory channels  Storage  Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD memory type SSD interface NVMe SSD form factor Optical drive type * Card reader integrated  Graphics  Discrete graphics card model * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model * Audio	Dual-channel  512 GB SSD 512 GB 1 512 GB TLC PCI Express 4.0  ✓ M.2  ×  X  Not available  ✓ Intel X Intel Graphics Intel Graphics	USB Power Delivery (USB PD)  Security  Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude  Certificates Compliance certificates  Certification  Weight & dimensions Width	<ul> <li>Kensington</li> <li>2.0</li> <li>✓</li> <li>BIOS, Power on, SSD, Supervisor</li> <li>5 - 35 °C</li> <li>5 - 43 °C</li> <li>8 - 95%</li> <li>5 - 95%</li> <li>3048 m</li> <li>RoHS</li> <li>ENERGY STAR® 8.0 EPEAT™ Gold Registered[3] ErP Lot 6/26 RoHS compliant TCO Certified 9.0 MIL-STD-810H</li> <li>315.9 mm</li> </ul>

