

Dahua Technology Entry DH-IPC-HFW1439S1-A-IL-0280B cámara de vigilancia Bala (forma) Cámara de seguridad IP Exterior 2560 x 1440 Pixeles Pared



Marca: Dahua Technology Familia de productos: Entry Código del producto: DH-IPC-HFW1439S1-A-IL-0280B

Nombre del producto : DH-IPC-HFW1439S1-A-IL-0280B

Dahua Technology Entry DH-IPC-HFW1439S1-A-IL-0280B. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Pared, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 94°, Ángulo de visión del objetivo, vertical: 51°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.9 mm (1 / 2.9"). Distancia de detección: 64 m, Distancia de observación: 25.6 m, Distancia de reconocimiento: 12.8 m

Performance		Video	
Type *	IP security camera	Gain control type	Auto/Manual
Placement supported * Connectivity technology *	Outdoor Wired	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Wide Dynamic Range (WDR)	√	Back Light Compensation (BLC)	✓
Day/night mode	1	Highlight Compensation (HLC)	✓
Dynamic range	120 dB	Region of Interest (ROI) encoding	✓
Design		Audio	
Form factor *	Bullet	Signal-to-Noise Ratio (SNR)	56 dB
Mounting type *	Wall	Built-in microphone	✓
Product colour *	White	Network	
Housing material	Metal, Plastic	Ethernet LAN *	/
International Protection (IP) code	IP67	Ethernet interface type	Fast Ethernet
Camera Minimum illumination Angle of rotation	0 lx	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; P2P
Lens viewing angle, horizontal	94°	Wi-Fi ∗	×
Lens viewing angle, vertical	51°	Bluetooth *	×
Lens viewing angle, diagonal Tilt angle range	110° 0 - 90°	Number of users	6 user(s)
Pan range	0 - 360°	Storage	
White balance	Auto, Manual, Natural, Outdoor,	Built-in HDD *	x
	Regional custom, Street lamp Electronic	ROM capacity	16 MB
Camera shutter type Camera shutter speed	1/3 - 1/100000 s	RAM capacity	64 MB
Number of Privacy masking areas	4	Security	
Image sensor		Video motion detection	✓
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Mirror	✓
Progressive scan	✓	Management features	
Sensor type *	CMOS	Web browser	✓
Lens system		Power	
Detect distance	64 m	Power source type *	DC, PoE
Observe distance	25.6 m	Power consumption (typical)	1.6 W
Recognize distance	12.8 m	Power consumption (max)	4.7 W
Identify distance Minimum aperture number	6.4 m 1.6	Power consumption (Power over Ethernet (PoE))	2 W
Fixed focal length	2.8 mm	DC output voltage	12
Closest focusing distance	1.1 m	Operational conditions	
		Operating temperature (T-T)	-40 - 60 °C

Night vision		Operational conditions	
Night vision * Night vision distance LED type	✓ 30 m IR/White	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 60 °C 0 - 95% 0 - 95%
Video		System requirements	
Maximum resolution *	2560 x 1440 pixels	Mobile operating systems supported Android, iOS	
Total megapixels *	4 MP	Weight & dimensions	
Video compression formats	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280	Width	162.6 mm
Supported graphics resolutions		Depth Height	70 mm 70 mm
			220 g
		Packaging data	
Noise reduction	✓	Package weight	350 g
Noise reduction technology	3D noise reduction	Packaging content	
		Number of cameras *	1

