



Dahua Technology CS4220-16GT-135 dispositivo de redes Gestionado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro

Marca : Dahua Technology

Código del producto: CS4220-16GT-135

Nombre del producto : CS4220-16GT-135

Dahua Technology CS4220-16GT-135. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 18. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 40 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE.... Energía sobre Ethernet (PoE). Montaje en rack

Management features		Design	
Switch type *	Managed	Housing material	Metal
Switch layer	L2	Reset button	✓
Web-based management	✓	Power	
Cloud-managed	✓	Power source *	AC
Ports & interfaces		AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports quantity *	18	AC input frequency	47/63 Hz
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Input current	3 A
Gigabit Ethernet (copper) ports quantity	18	Power consumption (typical)	154 W
SFP module slots quantity	2	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) ports quantity	16
		Total Power over Ethernet (PoE) budget	135 W
10G support *	✗	Operational conditions	
Flow control support	✓	Operating temperature (T-T)	-10 - 55 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	Storage temperature (T-T)	-40 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	5 - 95%
Number of VLANs	32	Storage relative humidity (H-H)	5 - 95%
Data transmission		Weight & dimensions	
Switching capacity *	40 Gbit/s	Width	440 mm
Forwarding rate	29.76 Mpps	Depth	220 mm
MAC address table *	8000 entries	Height	44 mm
Jumbo frames support	✓	Weight	2.26 kg
Jumbo frames	15000	Packaging data	
Packet buffer memory	4 MB	Package width	540 mm
Security		Package depth	342 mm
DHCP features	DHCP client	Package height	90 mm
Design		Package weight	2.91 kg
Rack mounting *	✓		
Product colour	Black		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date