



Dahua Technology DH-CS4010-8ET-60 dispositivo de redes Gestionado L2 Fast Ethernet (10/100) Energía sobre Ethernet (PoE) Negro



Marca : Dahua Technology

Código del producto: DH-CS4010-8ET-60

Nombre del producto : DH-CS4010-8ET-60

Dahua Technology DH-CS4010-8ET-60. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 8. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 4.8 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x. Voltaje de entrada DC: 53 V. Energía sobre Ethernet (PoE)

Management features		Design	
Switch type *	Managed	Product colour	Black
Switch layer	L2	Housing material	Metal
Quality of Service (QoS) support	✓	Reset button	✓
Web-based management	✓	LED indicators	✓
Cloud-managed	✓	Power	
Ports & interfaces		Power source *	DC/PoE
Basic switching RJ-45 Ethernet ports quantity *	8	Power supply included *	✓
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	Redundant power supply (RPS) support	✓
Fast Ethernet (copper) ports quantity	8	DC input voltage	53 V
Gigabit Ethernet (copper) ports quantity	2	Input current	1.226 A
Network		Power consumption (max)	65 W
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) ports quantity	8
Flow control support	✓	Operational conditions	
Ethernet LAN data rates	10,100,1000 Mbit/s	Operating temperature (T-T)	-10 - 55 °C
VLAN support	✓	Storage temperature (T-T)	-40 - 70 °C
Virtual LAN features	Port-based VLAN	Operating relative humidity (H-H)	5 - 95%
Number of VLANs	32	Storage relative humidity (H-H)	5 - 95%
Data transmission		Weight & dimensions	
Switching capacity *	4.8 Gbit/s	Width	130 mm
Forwarding rate	3.57 Mpps	Depth	90 mm
MAC address table *	8000 entries	Height	26 mm
Jumbo frames support	✓	Weight	280 g
Jumbo frames	9216	Packaging data	
Packet buffer memory	4 MB	Package width	265 mm
Security		Package depth	238 mm
DHCP features	DHCP client	Package height	76 mm
Design		Package weight	800 g
Rack mounting *	✗	Sustainability	
		Sustainability compliance	✓
		Certificates	
		Compliance certificates	CE

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date