

KYOCERA ECOSYS PA2100cx Color 1200 x 1200 DPI A4

Marca : KYOCERA

Familia de productos:
ECOSYS

Código del producto:
110C0C3NL0

Nombre del producto :
PA2100cx

KYOCERA ECOSYS PA2100cx. Tecnología de impresión: Laser, Color. Número de cartuchos de impresión: 4, Ciclo de trabajo (máximo): 65000 páginas por mes. Resolución máxima: 1200 x 1200 DPI. Tamaño máximo de papel ISO A-series: A4. Velocidad de impresión (negro, calidad normal, A4/US Carta): 21 ppm, Impresión a doble cara. Pantalla: LCD. Listo para redes. Color del producto: Negro, Blanco



Printing		Network	
Duplex printing mode	Auto	Network ready	✓
Print speed (colour, normal quality, A4/US Letter)	21 ppm	Wi-Fi *	✗
Colour *	✓	Ethernet LAN *	✓
Print technology *	Laser	Cabling technology	10/100/1000Base-T(X)
Duplex printing *	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Maximum resolution *	1200 x 1200 DPI	Near Field Communication (NFC)	✗
Print speed (black, normal quality, A4/US Letter) *	21 ppm	Bluetooth	✗
Warm-up time	32 s	Mobile printing technologies	Apple AirPrint, Kyocera Mobile Print, Mopria Print Service
Time to first page (black, normal)	11 s	Performance	
Time to first page (colour, normal)	12.5 s	Internal memory *	512 MB
Print margins (top, bottom, right, left)	4.2 mm	Maximum internal memory	512 MB
Watermark printing	✓	Card reader integrated	✗
Secure printing	✓	Built-in processor	✓
N-up printing	2, 4, 6, 8, 9, 16, 25	Processor family	ARM Cortex
Booklet printing function	✗	Processor frequency	800 MHz
Economical printing	✓	Sound pressure level (printing)	48 dB
Features		Sound power level (standby)	30 dB
Maximum duty cycle *	65000 pages per month	Design	
Recommended duty cycle	500 - 1500 pages per month	Market positioning *	Home & office
Printing colours *	Black, Cyan, Magenta, Yellow	Product colour *	Black, White
Number of print cartridges *	4	Built-in display *	✓
Page description languages *	PDF, PCL 6, XPS, PostScript 3	Display	LCD
Printer fonts	PCL, PostScript	Touchscreen	✗
Country of origin	China	Display number of lines	2 lines
		Control type	Buttons
		Certification	GS, TUV

Features		Certificates	
Replacement cartridges	TK-5430K Zwart (toner 1.250) ISO/IEC 19798 TK-5430Y Geel (toner 1.250) ISO/IEC 19798 TK-5430M Magenta (toner 1.250) ISO/IEC 19798 TK-5430C Cyaan (toner 1.250) ISO/IEC 19798 TK-5440K Zwart (toner 2.800) ISO/IEC 19798 TK-5440Y Geel (toner 2.400) ISO/IEC 19798 TK-5440M Magenta (toner 2.400) ISO/IEC 19798 TK-5440C Cyaan (toner 2.400) ISO/IEC 19798	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
		Power	
		Power consumption (printing) *	345 W
		Power consumption (ready)	33 W
		Power consumption (PowerSave)	0.9 W
		Power consumption (off)	0.2 W
		Energy Star Typical Electricity Consumption (TEC)	0.691 kWh/week
Input & output capacity		AC input voltage	220 - 240 V
Total number of input trays *	2	AC input frequency	50 - 60 Hz
Total input capacity *	300 sheets	System requirements	
Total output capacity *	150 sheets	Windows operating systems supported	✓
Paper tray 1 input capacity	250 sheets	Mac operating systems supported	✓
Multi-Purpose tray	✓	Linux operating systems supported	✓
Multi-Purpose tray input capacity	50 sheets	Weight & dimensions	
Maximum number of input trays	3	Width	410 mm
Maximum input capacity	550 sheets	Depth	410 mm
Maximum output capacity	150 sheets	Height	329 mm
Paper handling		Weight	26 kg
Maximum ISO A-series paper size *	A4	Packaging data	
Maximum print size	216 x 356 mm	Package width	592 mm
Paper tray media types *	Plain paper	Package depth	567 mm
Multi-purpose tray media types	Plain paper	Package height	460 mm
ISO A-series sizes (A0...A9) *	A4, A5, A6	Package weight	27 kg
ISO B-series sizes (B0...B9)	B5, B6	Packaging content	
Non-ISO print media sizes	Legal, Letter	Cartridge(s) included	✓
Custom media width	70 - 216 mm	Included cartridge capacity (black)	1500 pages
Custom media length	148 - 356 mm	Included cartridge capacity (CMY)	1500 pages
Paper tray media weight	60 - 163 g/m²	Cables included	AC
Multi-Purpose Tray media weight	60 - 220 g/m²	Logistics data	
Duplex media weight	60 - 120 g/m²	Harmonized System (HS) code	84433210
Ports & interfaces		Technical details	
Standard interfaces	Ethernet, USB 2.0	Compliance certificates	CE
Direct printing *	✓		
USB port *	✓		
USB 2.0 ports quantity	1		
USB connector	USB Type-A		



0632983074930



632983074930



0632983074923



632983074923

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.