

Allied Telesis AT-X530L-52GPX-90 dispositivo de redes Gestionado L3 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Gris



Marca : Allied Telesis

Código del producto: AT-X530L-52GPX-90

Nombre del producto : AT-X530L-52GPX-90

Allied Telesis AT-X530L-52GPX-90. Tipo de interruptor: Gestionado, Capa del interruptor: L3. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 48. Tabla de direcciones MAC: 16000 entradas, Capacidad de conmutación: 176 Gbit/s. Estándares de red: IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE.... Energía sobre Ethernet (PoE). Montaje en rack

Management features		Power	
Switch type *	Managed	Power supply included *	✓
Switch layer	L3	Number of power supply units	2
Ports & interfaces		AC input voltage	90 - 264 V
Basic switching RJ-45 Ethernet ports quantity *	48	AC input frequency	50/60 Hz
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power consumption (max)	950 W
Fiber ports quantity	4	Power over Ethernet (PoE)	
Fiber optic connector	SFP+	Power over Ethernet (PoE) *	✓
Network		Power over Ethernet (PoE) ports quantity	48
Networking standards *	IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Total Power over Ethernet (PoE) budget	740 W
		Operational conditions	
10G support *	✓	Operating temperature (T-T)	0 - 50 °C
VLAN support	✓	Storage temperature (T-T)	-25 - 70 °C
Number of VLANs	4094	Operating relative humidity (H-H)	5 - 90%
Data transmission		Storage relative humidity (H-H)	5 - 95%
Switching capacity *	176 Gbit/s	Operating altitude	0 - 3048 m
Forwarding rate	130.9 Mpps	Heat dissipation	324 BTU/h
MAC address table *	16000 entries	Weight & dimensions	
Packet buffer memory	3 MB	Width	441 mm
Design		Depth	421 mm
Rack mounting *	✓	Height	44 mm
Stackable *	✓	Weight	6.7 kg
Product colour	Grey	Packaging data	
Performance		Package width	577 mm
Memory type	DDR3-SDRAM	Package depth	548 mm
Internal memory	16000 MB	Package height	153 mm
Flash memory	256 MB	Package weight	8.9 kg
Noise level	42 dB		
Power			
Power source *	AC/PoE		



0767035217161



767035217161

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.