

Vertiv Liebert GXT5LI-1500LVRT2UXL sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 1.5 kVA 1350 W 6 salidas AC

Marca : Vertiv

Familia de productos: Liebert

Código del producto:
GXT5LI-1500LVRT2UXL

Nombre del producto :
GXT5LI-1500LVRT2UXL



Un UPS inteligente y eficiente para la protección de sus aplicaciones de misión crítica. 1500VA / 1350W, 120 V, convertible en rack/torre

Vertiv Liebert GXT5LI-1500LVRT2UXL sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 1.5 kVA 1350 W 6 salidas AC:

La tecnología de iones de litio ofrece una vida útil 2-3 veces mayor que las baterías de plomo-ácido junto con un menor costo total de propiedad. Esto hace que el UPS en línea Liebert® GXT5 con baterías de iones de litio sea ideal para salas de redes y de servidores, y otras aplicaciones de borde de misión crítica.

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	1.5 kVA	Rack capacity	2U
Output power *	1350 W	Cable length	3 m
Waveform *	Pure sine	Product colour *	Black
Input operation voltage (min) *	102 V	Operational conditions	
Input operation voltage (max) *	150 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	40 - 70 Hz	Storage temperature (T-T)	-20 - 60 °C
Output operation voltage (min)	100 V	Operating relative humidity (H-H)	10 - 50%
Output operation voltage (max)	125 V	Storage relative humidity (H-H)	0 - 95%
Noise level	48 dB	Operating altitude	0 - 3000 m
Ports & interfaces		Certificates	
AC outlet types	NEMA 5-15R	Compliance certificates	REACH, RoHS, WEEE
Power plug	NEMA 5-15P	Safety regulation & standards	
AC outlets quantity	6 AC outlet(s)	Safety	
Battery		UL 1642 (Li-Ion Battery Cells), UL 1973 (Li-Ion Battery Pack w/UPS), UL 1778, CSA 22.2 No. 107.3	
Battery technology	Lithium-Ion (Li-Ion)	Weight & dimensions	
Typical backup time at full load	14 min	Width	430 mm
Typical backup time at half load	28 min	Depth	475 mm
Battery recharge time	2 h	Height	85 mm
		Weight	18 kg
		Packaging data	
		Package width	570 mm
		Package depth	597 mm
		Package height	242 mm
		Package weight	24 kg



0767041034899



767041034899

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date