

## Vertiv Liebert GXT5LI-3000LVRT2UXL sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 3 kVA 2700 W 7 salidas AC

**Marca :** Vertiv

**Familia de productos:** Liebert

**Código del producto:**  
GXT5LI-3000LVRT2UXL

**Nombre del producto :**  
GXT5LI-3000LVRT2UXL

Vertiv Liebert GXT5LI-3000LVRT2UXL. Topología UPS: Doble conversión (en línea), Capacidad de potencia de salida (VA): 3 kVA, Potencia de salida: 2700 W. Tipo de salida AC: NEMA 5-15R, NEMA 5-20R, NEMA L5-30R, Conector: NEMA L5-30P, Cantidad de salidas AC: 7 salidas AC. Tecnología de batería: Fosfato de hierro-litio (LiFePO<sub>4</sub>), Tiempo típico de respaldo a carga completa: 6.5 min, Tiempo típico de respaldo a media carga: 15 min. Factor de forma: Montaje en rack/Torre o Montaje en bastidor/Torre, Color del producto: Negro, Capacidad del rack: 2U. Certificados de cumplimiento: REACH, RoHS, WEEE



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	15 min
Output power capacity *	3 kVA	Battery recharge time	2 h
Output power *	2700 W	Design	
Waveform *	Pure sine	Form factor *	Rackmount/Tower
Input operation voltage (min) *	102 V	Rack capacity	2U
Input operation voltage (max) *	150 V	Cable length	3 m
Input frequency *	40/70 Hz	Product colour *	Black
Output operation voltage (min)	100 V	Control type	Buttons
Output operation voltage (max)	125 V	LED indicators	✓
Output frequency	40/70 Hz	Operational conditions	
Response time	0 ms	Operating temperature (T-T)	0 - 40 °C
Noise level	48 dB	Storage temperature (T-T)	-20 - 60 °C
Ports & interfaces		Operating relative humidity (H-H)	0 - 95%
AC outlet types	NEMA 5-15R, NEMA 5-20R, NEMA L5-30R	Operating altitude	0 - 3000 m
Power plug	NEMA L5-30P	Certificates	
AC outlets quantity	7 AC outlet(s)	Compliance certificates	REACH, RoHS, WEEE
USB port	✓	Weight & dimensions	
USB port type	USB Type-B	Width	430 mm
Serial interface	✓	Depth	545 mm
Serial interface type	RS-232	Height	85 mm
Battery		Weight	22 kg
Battery technology	Lithium Iron Phosphate (LiFePO <sub>4</sub> )		

Battery		Packaging data	
Typical backup time at full load	6.5 min	Package width	570 mm
		Package depth	717 mm
		Package height	242 mm
		Package weight	27.1 kg



0767041034912



767041034912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-MAR-2025. Prints or copies of Information are only valid on the printed Publication date