

CyberPower CP1500PFCRM2U sistema de alimentación ininterrumpida (UPS) Línea interactiva 1.5 kVA 1000 W 8 salidas AC

Marca : CyberPower

Código del producto: CP1500PFCRM2U

Nombre del producto : CP1500PFCRM2U



CyberPower CP1500PFCRM2U. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 1.5 kVA, Potencia de salida: 1000 W. Tipo de salida AC: NEMA 5-15R, Conector: NEMA 5-15P, Cantidad de salidas AC: 8 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Capacidad de la batería: 9 Ah, Voltaje de la pila: 12 V. Factor de forma: Montaje en rack o Montaje en bastidor, Color del producto: Negro, Material de la cubierta: Plástico. Certificados de cumplimiento: RoHS



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at half load	10.2 min
Output power capacity *	1.5 kVA	Battery recharge time	8 h
Output power *	1000 W	Hot-swap battery	✓
Waveform *	Sine	Design	
Input operation voltage (min) *	88 V	Form factor *	Rackmount
Input operation voltage (max) *	144 V	Housing material	Plastic
Input frequency *	57/63 Hz	Rack capacity	2U
Output voltage regulation	11%	Product colour *	Black
Surge energy rating	1500 J	Display type	LCD
Output power factor	0.7	Operational conditions	
Audible alarm(s)	✓	Operating temperature (T-T)	0 - 40 °C
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Storage temperature (T-T)	-15 - 45 °C
Ports & interfaces		Operating relative humidity (H-H)	0 - 95%
AC outlet types	NEMA 5-15R	Certificates	
Power plug	NEMA 5-15P	Compliance certificates	RoHS
AC outlets quantity	8 AC outlet(s)	Sustainability	
USB port	✓	Sustainability certificates	ENERGY STAR
Serial interface	✓	Weight & dimensions	
Battery		Width	432 mm
Battery technology	Sealed Lead Acid (VRLA)	Depth	267 mm
Battery capacity	9 Ah	Height	86 mm
Battery voltage	12 V	Weight	12.2 kg
Number of batteries supported	2	Packaging data	
Typical backup time at full load	3.1 min	Package width	373.4 mm
		Package depth	523.2 mm
		Package height	162.6 mm

Packaging data

Package weight	13.4 kg
----------------	---------



0649532934621



649532934621

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date