



Dahua Technology DHI-VT02111D-P-S3 sistema de intercomunicación de video 2 MP 17.8 cm (7") Negro

Marca : Dahua Technology

Código del producto: DHI-VT02111D-P-S3

Nombre del producto : DHI-VT02111D-P-S3

Dahua Technology DHI-VT02111D-P-S3. Diagonal de la pantalla: 17.8 cm (7"), Tecnología de visualización: TFT, Resolución de la pantalla: 1024 x 600 Píxeles. Megapíxeles: 2 MP, Formato de vídeo soportado: 720p, 1080p, Tipo de sensor: CMOS. Tipo de LED: IR. Codecs de voz: G.711a, G.711u, PCM. Color del producto: Negro, Código IP (International Protection): IP65, Material de la cubierta: Acrilonitrilo butadieno estireno (ABS), Policarbonato (PC)

Technical details		Audio	
Connectivity technology *	Wired	Voice codecs	G.711a, G.711u, PCM
Speakerphone *	✓	Design	
Number of displays supported *	1	Product colour *	Black
Maximum number of cameras supported *	1	International Protection (IP) code	IP65
Door station control	✓	Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)
Wall mountable	✓	Storage	
Built-in microphone	✓	Memory card slot	✓
Certification	CE; FCC	Compatible memory cards	SD
Display		Maximum memory card size	8 GB
Display diagonal *	17.8 cm (7")	Indoor unit	
Display technology	TFT	RS-485 ports	1
Display resolution	1024 x 600 pixels	Network	
Touchscreen	✓	Ethernet interface type	Fast Ethernet
Touchscreen type	Capacitive	Ethernet LAN data rates	10,100 Mbit/s
Wide Dynamic Range (WDR)	✓	Ethernet LAN (RJ-45) ports	6
Camera		Power over Ethernet (PoE)	✓
Megapixel (approx.)	2 MP	Supported network protocols	SIP; P2P; IPv4; DNS; RTSP; RTP; TCP; UDP
Supported video modes	720p, 1080p	Software	
Sensor type	CMOS	Operating system installed	Embedded LINUX
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Power	
Maximum frame rate	30 fps	Indoor unit power type	DC/PoE
Viewing angle, horizontal	107°	Outdoor unit power type	DC/PoE
Viewing angle, vertical	60°	Power consumption (typical)	5 W
Viewing angle, diagonal	122°	Power consumption (standby)	1 W
Day/night mode	✓	Operational conditions	
Night vision		Operating temperature (T-T)	-30 - 60 °C
Night vision	✓	Operating relative humidity (H-H)	10 - 90%
LED type	IR	Packaging data	
Audio		Indoor unit included *	✓
Built-in speaker(s)	✓	Outdoor unit included *	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date