



Dahua Technology Pro HAC-T1A21 cámara de vigilancia Domo

Cámara de seguridad IP Interior y exterior 1920 x 1080 Píxeles Techo

Marca : Dahua Technology

Familia de productos: Pro

Código del producto: HAC-T1A21

Nombre del producto : HAC-T1A21



Dahua Technology Pro HAC-T1A21. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Domo. Iluminación mínima: 0.04 Lux, Ángulo de campo de visión (FOV): 93°, Ángulo de rotación: 360°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"), Número de píxeles efectivos (A x V): 1920 x 1080 Píxeles. Intervalo de longitud focal: 3.6 - 2.8 mm

Performance		Video	
Type *	IP security camera	NTSC resolutions	1920 x 1080 pixels
Placement supported *	Indoor & outdoor	PAL resolutions	1920 x 1080 pixels
Connectivity technology *	Wired	Gain control type	Auto
PTZ control	✓	Back Light Compensation (BLC)	✓
Wide Dynamic Range (WDR)	✓	Highlight Compensation (HLC)	✓
Day/night mode	✓	Digital Wide Dynamic Range (DWDR)	✓
Languages support	Multi	Smart IR	✓
Design		Network	
Form factor *	Dome	Ethernet LAN *	✗
Mounting type *	Ceiling	Wi-Fi *	✗
Product colour *	White	Bluetooth *	✗
Housing material	Plastic	Storage	
Camera		Built-in HDD *	✗
Camera pan control	✓	Ports & interfaces	
Camera tilt control	✓	BNC output ports	1
Minimum illumination	0.04 lx	DC-in jack	✓
Field of view (FOV) angle	93°	Power	
Angle of rotation	360°	Power source type *	DC
Tilt angle range	0 - 78°	Power consumption (max)	2.3 W
Pan range	0 - 360°	DC output voltage	12
Camera shutter type	Electronic	Operational conditions	
Camera shutter speed	1/100000 s	Operating temperature (T-T)	-40 - 60 °C
Image sensor		Storage temperature (T-T)	-40 - 60 °C
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Operating relative humidity (H-H)	0 - 95%
Progressive scan	✓	Storage relative humidity (H-H)	0 - 95%
Sensor type *	CMOS	Weight & dimensions	
Number of effective pixels (H x V)	1920 x 1080 pixels	Height	69 mm
Lens system		Diameter	8.5 cm
Focal length range	3.6 - 2.8 mm	Weight	90 g
Maximum aperture number	1.85	Packaging data	
Night vision		Package weight	130 g
Night vision *	✓	Package type	Box
LED type	IR	Packaging content	
Video		Number of cameras *	1
Maximum resolution *	1920 x 1080 pixels		
Total megapixels *	2 MP		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date