



TP-Link Tapo C210P2 Esférico Cámara de seguridad IP Interior 2304 x 1296 Píxeles Escritorio

Marca : TP-Link

Familia de productos: Tapo

Código del producto: TAPO
C210P2

Nombre del producto : Tapo
C210P2

TP-Link Tapo C210P2. Tipo: Cámara de seguridad IP, Colocación compatible: Interior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Escritorio, Color del producto: Blanco, Negro, Factor de forma: Esférico. Ángulo de campo de visión (FOV): 98°. Distancia focal fija: 4 mm. Distancia de visión nocturna: 10 m, Longitud de onda infraroja: 850 nm



| Performance | | Storage | |
|---------------------------|--|-----------------------------------|----------------------|
| Type * | IP security camera | Built-in HDD * | ✗ |
| Placement supported * | Indoor | Card reader integrated | ✓ |
| Connectivity technology * | Wired | Compatible memory cards | MicroSD (TransFlash) |
| Day/night mode | ✓ | Maximum memory card size | 512 GB |
| Design | | Ports & interfaces | |
| Form factor * | Spherical | DC-in jack | ✓ |
| Mounting type * | Desk | Security | |
| Product colour * | White, Black | Video motion detection | ✓ |
| LED indicators | ✓ | Security algorithms | AES |
| Camera | | Management features | |
| Field of view (FOV) angle | 98° | Reset button | ✓ |
| Lens system | | Power | |
| Maximum aperture number | 2 | Power source type * | DC |
| Fixed focal length | 4 mm | AC input voltage | 100 - 240 V |
| Night vision | | AC input frequency | 50 / 60 Hz |
| Night vision * | ✓ | DC output voltage | 9 |
| Night vision distance | 10 m | DC output current | 0.6 A |
| Infra-red wavelength | 850 nm | Operational conditions | |
| Video | | Operating temperature (T-T) | 0 - 40 °C |
| Maximum resolution * | 2304 x 1296 pixels | Storage temperature (T-T) | -20 - 60 °C |
| Video formats supported | H.264 | Operating relative humidity (H-H) | 10 - 90% |
| Frame rate | 15 fps | Storage relative humidity (H-H) | 5 - 90% |
| Audio | | Weight & dimensions | |
| Built-in speaker(s) | ✓ | Width | 85.4 mm |
| Built-in microphone | ✓ | Depth | 86.8 mm |
| Network | | Height | 117.7 mm |
| Ethernet LAN * | ✗ | Packaging content | |
| Networking standards | IEEE 802.11b, IEEE 802.11g, IEEE 802.11n | Number of cameras * | 1 |
| Wi-Fi * | ✓ | Manual | ✓ |
| Wi-Fi standards | 802.11b, 802.11g, Wi-Fi 4 (802.11n) | | |
| Bluetooth * | ✗ | | |
| Live view | ✓ | | |



4895252500233

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date