

ASUS TUF-GAMING-1200G unidad de fuente de alimentación 1200 W 20+4 pin ATX Negro

Marca : ASUS

Código del producto: TUF-GAMING-1200G

Nombre del producto : TUF-GAMING-1200G

ASUS TUF-GAMING-1200G. Potencia total: 1200 W, Voltaje de entrada AC: 100 - 240 V, Potencia combinada (3,3 V): 130 W. Alimentador de energía para tarjeta madre: 20+4 pin ATX, Longitud del cable de alimentación de la placa base: 61 cm, Longitud del cable de alimentación SATA: 120,400 mm. Utilizar con: PC, Certificación 80 PLUS: 80 PLUS Gold, Formas de factor de tarjeta madre soportadas: ATX. Color del producto: Negro, Tipo de enfriamiento: Activo, Diámetro de ventilador: 13.5 cm. Ancho: 150 mm, Profundidad: 150 mm, Altura: 86 mm



Control de energía		Puertos e Interfaces	
Potencia total *	1200 W	Longitud del cable de alimentación periférico (Molex)	150,400 mm
Voltaje de entrada AC *	100 - 240 V	Conector de energía EPS (8-pin)	✓
Potencia combinada (3,3 V)	130 W	Conectores de poder PCI Express (8 pin)	3
Potencia combinada (+12 V)	1188 W	Conectores de alimentación PCI Express (16 pines)	2
Potencia combinada (+5 V)	130 W	Longitud del cable de alimentación PCI Express	67.5 cm
Potencia combinada (-12V)	9.6 W	CPU conector de alimentación (4 +4 pines)	✓
Potencia combinada (+5 VSB)	15 W	Longitud del cable de alimentación CPU	65 cm
Corriente máxima de salida (+3.3V)	25 A	Tipo de cableado	Totalmente modular
Corriente máxima de salida (+12V)	99 A	Desempeño	
Corriente máxima de salida (+5V)	25 A	Certificación 80 PLUS *	80 PLUS Gold
Corriente máxima de salida (-12V)	0.8 A	Formas de factor de tarjeta madre soportadas	ATX
Corriente máxima de salida (+5Vsb)	3 A	Utilizar con *	PC
Funciones de protección de poder	Sobrecorriente, Sobretensión, Sobrevoltaje, Cortocircuito, Bajo voltaje	Diseño	
Puertos e Interfaces		Color del producto	Negro
Alimentador de energía para tarjeta madre *	20+4 pin ATX	Tipo de enfriamiento	Activo
Longitud del cable de alimentación de la placa base	61 cm	Diámetro de ventilador	13.5 cm
Número de conectores de energía SATA	5	Peso y dimensiones	
Longitud del cable de alimentación SATA	120,400 mm	Ancho	150 mm
Conectores de poder (4 pin) periféricos (Molex) *	4	Profundidad	150 mm
		Altura	86 mm
		Peso	2.66 kg

Detalles técnicos

Certificados de cumplimiento RoHS



0195553786324



195553786324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-SEP-2024. Prints or copies of Information are only valid on the printed Publication date