

## BenQ RD280U monitor de computadora 71.6 cm (28.2") 3840 x 2560 Pixeles 4K Ultra HD Negro

Marca : BenQ Código del producto: 9H.LM1LJ.TBA

Nombre del producto: RD280U

- 71.6cm (28.2") 4K Ultra HD 3840 x 2560 IPS
- 5ms, 3:2, 350cd/m², 1200:1
- USB, HDMI, DisplayPort

71.6cm (28.2") 4K Ultra HD 3840 x 2560 IPS, 3:2, 350cd/m², 1.07B, 5ms, 178°/178°, 1200:1 BenQ RD280U. Diagonal de la pantalla: 71.6 cm (28.2"), Resolución de la pantalla: 3840 x 2560 Pixeles, Tipo HD: 4K Ultra HD, Tiempo de respuesta: 5 ms, Relación de aspecto nativa: 3:2, Ángulo de visión, horizontal: 178°, Ángulo de visión, vertical: 178°. Altavoces incorporados. Concentrador USB integrado, Versión del concentrador USB: 3.2 Gen 1 (3.1 Gen 1). montaje VESA, Ajustes de altura. Color del producto: Negro





Display		Ports & interfaces	
. ,			
Display diagonal *	71.6 cm (28.2")	DisplayPorts quantity	1
Display resolution *	3840 x 2560 pixels	DisplayPort version	1.4
HD type *	4K Ultra HD	Headphone out *	✓
Native aspect ratio *	3:2	Headphone outputs	1
Panel type *	IPS	Built-in KVM switch	<b>✓</b>
LED backlight	✓	HDCP	✓
Touchscreen *	×	HDCP version	2.2
Display brightness (peak)	400 cd/m²	Ergonomics	
Display brightness (typical)	350 cd/m <sup>2</sup>	•	
Response time *	5 ms	VESA mounting *	<b>✓</b>
Anti-glare screen	✓	Panel mounting interface	100 x 100 mm
Screen shape *	Flat	Wall mountable	✓
Contrast ratio (typical) *	1200:1	Cable lock slot *	×
Maximum refresh rate *	60 Hz	Height adjustment *	✓
Viewing angle, horizontal	178°	Adjustable height (max)	11 cm
Viewing angle, vertical	178°	Pivot	✓
Display number of colours *	1.07 billion colours	Pivot angle	0 - 90°
Pixel density	164 ppi	Swivelling	/
Display diagonal (metric)	72 cm	Swivel angle range	-15 - 15°
High Dynamic Range (HDR) supported	✓	Tilt adjustment	<b>✓</b>
High Dynamic Range (HDR)	DisplayHDR 400, High Dynamic	Tilt angle range	-5 - 20°
technology	Range 10 (HDR10)	On Screen Display (OSD)	✓
Colour gamut standard	DCI-P3		Arabic, Simplified Chinese,
Colour gamut	95%		Traditional Chinese, Czech, German,
Performance		On Screen Display (OSD) languages	Dutch, English, Spanish, French, Hungarian, Italian, Japanese,
Flicker-free technology	✓		Korean, Polish, Portuguese, Romanian, Russian, Swedish
Low Blue Light technology	<b>✓</b>		

Performance		Power	
Smart modes	ePaper	Energy efficiency class (SDR) *	G
Multimedia		Energy efficiency class (HDR) *	G
Number of speakers	2	Energy consumption (SDR) per 1000 hours *	29 kWh
RMS rated power Built-in speaker(s) *	4 W ✓	Energy consumption (HDR) per 1000 hours *	31 kWh
Built-in camera *	×	Power consumption (typical) *	34 W
		Power consumption (standby) *	0.4 W
Design		Power consumption (max)	205 W
Market positioning *	Business	Power consumption (off)	0.3 W
Product colour *	Black	AC input voltage	100 - 240 V
Ports & interfaces		Power supply type	Internal
Built-in USB hub *	✓	Energy efficiency scale	A to G
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Weight & dimensions	
Number of USB Type-B upstream ports quantity	1	Width (with stand) Depth (with stand)	610.4 mm 244.5 mm
USB Type-A downstream ports quantity	3	Height (with stand)	474.3 mm
USB Type-C downstream ports quantity	1	Weight (with stand) Width (without stand)	10.4 kg 610.4 mm
USB Type-C DisplayPort Alternate Mode	✓	Depth (without stand) Height (without stand)	87.1 mm 427.8 mm
USB Power Delivery (USB PD)	✓	Weight (without stand)	7.5 kg
USB Power Delivery up to	90 W	Packaging content	
HDMI *	✓	Quick start guide	/
HDMI ports quantity	1	Bundled software	Display Pilot 2
HDMI version	2.0		Display Filot 2
		Sustainability	
		Sustainability certificates	ENERGY STAR, EPEAT Bronze, TCO

