

DELL E Series E2225H monitor de computadora 54.5 cm (21.4") 1920 x 1080 Pixeles Full HD LCD Negro

Marca : DELL Familia de productos: E Código del producto: E2225H

Series

Nombre del producto:

E2225H

- 54.5cm (21.45") Full HD 1920 x 1080 Edge LED VA
- 8ms, 16:9, 250cd/m², 3000:1
- VGA, DisplayPort

54.5cm (21.45") Full HD 1920 x 1080 Edge LED VA, 16:9, 250cd/m², 16.7M, 8ms, 178°/178°, 3000:1 DELL E Series E2225H. Diagonal de la pantalla: 54.5 cm (21.4"), Resolución de la pantalla: 1920 x 1080 Pixeles, Tipo HD: Full HD, Tecnología de visualización: LCD, Tiempo de respuesta: 8 ms, Relación de aspecto nativa: 16:9, Ángulo de visión, horizontal: 178°, Ángulo de visión, vertical: 178°. montaje VESA. Color del producto: Negro





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type *	54.5 cm (21.4") 1920 x 1080 pixels Full HD 16:9 LCD VA	Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play LED indicators	✓ -5 - 21° ✓ ✓
LED backlight Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen Screen shape * Supported graphics resolutions	Edge LED X 250 cd/m² 8 ms Flat 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600 x 900, 1920 x 1080 (HD 1080) 480p, 576p, 720p, 1080p	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Power supply type	D Not available 12 kWh 11.9 W 0.3 W 19 W 0.3 W 100 - 240 V 50/60 Hz Internal
Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density	3000:1 75 Hz 178° 178° 16.7 million colours 5 ms 0.2493 x 0.241 mm 103 ppi	Energy efficiency scale Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	A to G 0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Display diagonal (metric)	30 - 84 kHz 50 - 76 Hz 47.9 cm 26 cm 544.85 cm	Weight & dimensions Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	504.3 mm 171 mm 384.2 mm 2.67 kg

Display		Weight & dimensions	
High Dynamic Range (HDR) supported Surface hardness NTSC coverage (typical)	X 3H 83%	Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	504.3 mm 49.6 mm 295.4 mm 2.34 kg
Performance		Bezel width (side)	1.28 cm
NVIDIA G-SYNC * AMD FreeSync *	× ×	Bezel width (top) Bezel width (bottom)	1.28 cm 1.69 cm
Flicker-free technology	✓	Packaging data	
Low Blue Light technology	✓	Package weight	4.18 kg
Multimedia		Packaging content	
Built-in speaker(s) * Built-in camera *	× ×	Stand included Cables included Quick start guide	AC, DisplayPort, VGA
Design		Power cable length	1.8 m
Market positioning * Product colour * Front bezel colour Detachable stand	Home Black Black	Sustainability Sustainability certificates Doesn't contain	ENERGY STAR, TCO Arsenic, Mercury, PVC/BFR
Feet colour	Black	Carbon footprint	
Ports & interfaces		Total carbon footprint (kg of CO2e)	124
Built-in USB hub * VGA (D-Sub) ports quantity	x 1	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of	56 8
HDMI * DisplayPorts quantity DisplayPort version	X 1 1.2	CO2e) Carbon emissions, energy usage (kg of CO2e)	59
Headphone out *	×	Carbon emissions, end-of-life (kg of CO2e)	1
HDCP HDCP version	✓ 1.4	Total carbon emissions, w/o use phase (kg of CO2e)	65
	1.4	PAIA version	GaBi version 1, 2024
Network		Other features	
Wi-Fi	X	Compliance certificates	RoHS
Ergonomics			
VESA mounting * Panel mounting interface Wall mountable Cable lock slot *	100 x 100 mm		
555.5 IOCK 5100	=		

Cable lock slot type

Height adjustment *

Pivot

Swivelling

Kensington

×

×



5397184822173

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.