![Dahua Technology logo]

Dahua Technology WizSense DH-SD3C205DB-GNY-A-PV cámara de vigilancia Domo Cámara de seguridad IP Interior y exterior 1920 x 1080 Pixeles Techo/pared/Tubo

Marca : Dahua Technology

Familia de productos: WizSense

Código del producto: DH-SD3C205DB-GNY-A-PV

Nombre del producto : DH-SD3C205DB-GNY-A-PV

Dahua Technology WizSense DH-SD3C205DB-GNY-A-PV. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Negro, Gris, Factor de forma: Domo. Ángulo de inclinación: -15 - 90°, Velocidad de inclinación: 27.1 °/seg, Velocidad de inclinación manual: 0.1 - 28.5 °/seg. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Zoom óptico: 5x, Zoom digital: 16x, Distancia de detección: 186.2 m

Performance

Type *	IP security camera
Placement supported *	Indoor & outdoor
Connectivity technology *	Wired
PTZ control	✔
PTZ modes	Preset point
Preset points	✔
Wide Dynamic Range (WDR)	✔
Day/night mode	✔
Alarm input/output	✔

Design

Form factor *	Dome
Mounting type *	Ceiling/Wall/Pole
Product colour *	Black, Grey
International Protection (IP) code	IP66

Camera

Camera pan control	✔
Camera tilt control	✔
Minimum illumination	0 lx
Tilt angle range	-15 - 90°
Tilt speed	27.1 °/sec
Tilt manual speed	0.1 - 28.5 °/sec
Pan range	0 - 355°
Pan speed	35.7 °/sec
Pan manual speed	0.1 - 36 °/sec
White balance	Auto, Halogen, Indoor, Manual, Outdoor, Street lamp
Camera shutter speed	1 - 1/30000 s

Image sensor

Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	✔
Sensor type *	CMOS

Lens system

Optical zoom	5x
Digital zoom	16x
Detect distance	186.2 m
Observe distance	73.5 m
Recognize distance	37.2 m
Focal length range	2.7 - 13.5 mm

Video

Maximum resolution *	1920 x 1080 pixels
Total megapixels *	2 MP
Video formats supported	H.264, H.264+, H.264B, H.265, H.265+
Frame rate	30 fps
Gain control type	Auto/Manual
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Back Light Compensation (BLC)	✔
Highlight Compensation (HLC)	✔
Region of Interest (ROI) encoding	✔

Audio

Built-in speaker(s)	✔
Signal-to-Noise Ratio (SNR)	55 dB
Built-in microphone	✔
Voice codecs	G.711Mu, G.711a, G.722.1, G.726

Network

Ethernet LAN *	✔
Supported network protocols	FTP; RTMP; IPv6; Bonjour; IPv4; DNS; RTCP; PPPoE; NTP; RTP; 802.1x; HTTPS; SNMP; TCP/IP; DDNS; UPnP; NFS; ICMP; UDP; IGMP; SMB; HTTP; SSL; DHCP; SMTP; Qos; RTSP; ARP

Storage

Card reader integrated	✔
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB

Ports & interfaces

Ethernet LAN (RJ-45) ports	1

Security

Alarm input channels	1
Alarm output channels	1

Power

Power source type *	DC, PoE
Power consumption (typical)	3 W
Power consumption (max)	12 W
DC output voltage	12

Lens system

Identify distance	18.6 m

Night vision

Night vision *	✔
Night vision distance	50 m
LED type	IR/White

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Operating relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	142.6 mm
Depth	140 mm
Height	236.2 mm
Weight	1.1 kg
Weight (with stand)	1.7 kg

Packaging content

Number of cameras *	1

6923172572684