

Dahua Technology PFS3110-8GT-65 dispositivo de redes No administrado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro

Marca: Dahua Technology Código del producto: PFS3110-8GT-65

Nombre del producto: PFS3110-8GT-65

Dahua Technology PFS3110-8GT-65. Tipo de interruptor: No administrado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 9. Capacidad de conmutación: 20 Gbit/s. Estándares de red: IEEE 802.3af, IEEE 802.3at. Energía sobre Ethernet (PoE)

Management features		Power	
Switch type * Switch layer	Unmanaged L2	Power supply included * AC input voltage	√ 100 - 240 V
Ports & interfaces		AC input frequency	50/60 Hz
Basic switching RJ-45 Ethernet ports quantity *	9	Power consumption (typical) Power consumption (max)	1.8 W 65 W
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
SFP module slots quantity	1	Power over Ethernet (PoE) *	✓
Fiber optic connector	SFP	Power over Ethernet (PoE) ports quantity	8
Network		Total Power over Ethernet (PoE)	65 W
Networking standards *	IEEE 802.3af, IEEE 802.3at	budget	05 VV
10G support *	×	Operational conditions	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-TX	Operating temperature (T-T) Operating relative humidity (H-H)	-10 - 55 °C 5 - 95%
Cable types supported Ethernet LAN data rates	Cat5, Cat5e, Cat6 10,100,1000 Mbit/s	Weight & dimensions	
Data transmission		Width	118 mm
Switching capacity * Forwarding rate Packet buffer memory	20 Gbit/s 14.88 Mpps 1.5 MB	Depth Height Weight	243 mm 35 mm 800 g
,	1.5 MB	Packaging data	
Design Product colour	Black	Package width	260 mm
	DIACK	Package depth	300 mm
Power		Package height	70 mm
Power source *	AC	Package weight	1.8 kg

