

CyberPower OLS10KERT5U-NEMA sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 10 kVA 10000 W 4 salidas AC

Marca : CyberPower

Código del producto: OLS10KERT5U-NEMA

Nombre del producto : OLS10KERT5U-NEMA



- Topología Doble Conversión en Línea
 - Alto factor de potencia a la salida
 - Protección contra sobrecargas
 - UPS Parallel Expansion (Optional)
 - Detección automática del módulo de batería extendida
 - Baterías sustituibles por el usuario
 - Panel LCD inclinable
 - Relé de contacto seco
 - Capacidad de gestión remota SNMP / HTTP (opcional)
 - Configuraciones convertibles en rack/torre
 - Modo ECO
 - Salida de onda senoidal pura
 - Tiempo de transferencia cero
 - Módulo de batería extendida (EBM)
 - Corriente de carga ajustable
 - Panel LCD a color
 - Puerto (EPO) de apagado de emergencia
 - Software de gestión PowerPanel
 - Servicio PowerPanel Cloud
- 10000 Watts, NEMA L6-20R x 2, NEMA L6-30R x 2, 1335 Joules



Features		Battery	
UPS topology *	Double-conversion (Online)	Number of batteries supported	10
Output power capacity *	10 kVA	Typical backup time at full load	2.9 min
Output power *	10000 W	Typical backup time at half load	11.2 min
Waveform *	Pure sine	Battery recharge time	4 h
Input operation voltage (min) *	110 V	Charging current	4 A
Input operation voltage (max) *	300 V	Design	
Input frequency *	50/60 Hz	Form factor *	Rackmount/Tower
Output operation voltage (min)	200 V	Housing material	Metal
Output operation voltage (max)	240 V	Rack capacity	5U
Output frequency	50/60 Hz	Product colour *	Black
Maximum current	49.5 A	Display type	LCD
Surge energy rating	1335 J	LED indicators	Operation
Response time	0 ms	Operational conditions	
Efficiency (ECO mode)	98%	Operating temperature (T-T)	0 - 40 °C
Power factor	1	Storage temperature (T-T)	-15 - 45 °C
Input power factor	0.99	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Operating altitude	0 - 1000 m
Output voltage Total Harmonic Distortion (THD)	3%	Non-operating altitude	0 - 15000 m
EMI/RFI noise filtering	✓	Certificates	
Surge protection	✓	Certification	CE, RoHS
Power protection features	Overload	Packaging content	
Audible alarm(s)	✓	Cables included	USB cable
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Weight & dimensions	
Ports & interfaces		Width	433 mm
AC outlet types	NEMA L6-20R, NEMA L6-30R	Depth	661 mm
		Height	213.5 mm

Ports & interfaces		Weight & dimensions	
AC outlets quantity	4 AC outlet(s)	Weight	78 kg
USB port	✓	Packaging data	
Serial interface type	RS-232	Package width	489 mm
Serial ports quantity	1	Package depth	890 mm
Battery		Package height	575 mm
Battery technology	Sealed Lead Acid (VRLA)	Package weight	86 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-APR-2025. Prints or copies of Information are only valid on the printed Publication date