

HiLook THC-T120-PC cámara de vigilancia Domo Cámara de seguridad CCTV Interior 1920 x 1080 Pixeles Techo

Marca : HiLook

Código del producto: THC-T120-PC

Nombre del producto : THC-T120-PC



2 MP EXIR, 1920 x 1080, 0.02 Lux, IR, PAL/NTSC

HiLook THC-T120-PC cámara de vigilancia Domo Cámara de seguridad CCTV Interior 1920 x 1080 Pixeles Techo:

Cámaras de luz híbridas inteligentes

Las cámaras de luz híbridas inteligentes Turbo HD de Hikvision vienen equipadas con iluminación suplementaria inteligente, IR y visible, que ofrece imágenes coloridas en HD 3K incluso por la noche cuando se detecta información clave.

HiLook THC-T120-PC. Tipo: Cámara de seguridad CCTV, Colocación compatible: Interior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Domo. Iluminación mínima: 0.02 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 103°. Tipo de sensor: CMOS, Número de píxeles efectivos (A x V): 1920 x 1080 Pixeles. Distancia focal fija: 2.8 mm

Performance		Night vision	
Type *	CCTV security camera	LED type	IR
Placement supported *	Indoor	Video	
Connectivity technology *	Wired	Maximum resolution *	1920 x 1080 pixels
Day/night mode	✓	Total megapixels *	2 MP
Languages support	English	Supported video modes	1080p
Design		Analog signal format system	NTSC, PAL
Form factor *	Dome	Gain control type	Auto
Mounting type *	Ceiling	Image quality adjustment	Brightness, DNR, Mirror, Sharpness
Product colour *	White	Back Light Compensation (BLC)	✓
Housing material	Plastic	Digital Wide Dynamic Range (DWDR)	✓
Camera		Network	
Camera pan control	✓	Ethernet LAN *	✗
Camera tilt control	✓	Wi-Fi *	✗
Minimum illumination	0.02 lx	Bluetooth *	✗
Angle of rotation	360°	Storage	
Lens viewing angle, horizontal	103°	Built-in HDD *	✗
Lens viewing angle, vertical	80.7°	Power	
Tilt angle range	0 - 75°	Power source type *	DC
Pan range	0 - 360°	Power consumption (max)	4 W
Camera shutter speed	1/25 - 1/50000 s	DC output voltage	12
Image sensor		Operational conditions	
Number of sensors	1	Operating temperature (T-T)	-40 - 60 °C
Sensor type *	CMOS	Operating relative humidity (H-H)	0 - 90%
Number of effective pixels (H x V)	1920 x 1080 pixels	Weight & dimensions	
Lens system		Height	76.1 mm
Number of lenses *	1	Diameter	8.54 cm
Fixed focal length	2.8 mm	Weight	130 g
Night vision		Packaging content	
Night vision *	✓	Number of cameras *	1
Night vision distance	20 m		



6954273688400

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date