



## Dahua Technology DHI-NVR5216-16P-EI grabadora de vídeo en red (NVR)

**Marca :** Dahua Technology

**Código del producto:** DHI-NVR5216-16P-EI

**Nombre del producto :** DHI-NVR5216-16P-EI

Dahua Technology DHI-NVR5216-16P-EI. Canales de entrada de vídeo: 16 canales, Máxima resolución: 3840 x 2160 Píxeles, Formatos de audio soportados: G.711u, PCM. Protocolos de red compatibles: HTTP; HTTPS; TCP/IP; IPv4; UDP; NTP; DHCP; DNS; SMTP; UPnP; DDNS; Alarm Server; IP Search.... Voltaje de entrada AC: 100 - 240 V, Frecuencia de entrada AC: 47 - 63 Hz. Ancho: 375 mm, Profundidad: 329.3 mm, Altura: 53 mm

| Performance                |                              | Ports & interfaces                |                                                                                                                                                                                |
|----------------------------|------------------------------|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video input channels *     | 16 channels                  | RS-232 interface                  | ✓                                                                                                                                                                              |
| Alarm input channels       | 4                            | Supported network protocols       | HTTP; HTTPS; TCP/IP; IPv4; UDP; NTP; DHCP; DNS; SMTP; UPnP; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); Multicast; P2P; Auto Registration; iSCSI |
| Alarm output channels      | 2                            |                                   |                                                                                                                                                                                |
| Maximum resolution *       | 3840 x 2160 pixels           |                                   |                                                                                                                                                                                |
| Audio formats supported    | G.711u, PCM                  |                                   |                                                                                                                                                                                |
| Video formats supported    | H.264, H.264+, H.265, H.265+ |                                   |                                                                                                                                                                                |
| Image formats supported    | MJPEG                        |                                   |                                                                                                                                                                                |
| Face detection             | ✓                            |                                   |                                                                                                                                                                                |
| Hard drive                 |                              | Power                             |                                                                                                                                                                                |
| Number of HDDs installed * | 2                            | AC input voltage                  | 100 - 240 V                                                                                                                                                                    |
| Ports & interfaces         |                              | AC input frequency                | 47 - 63 Hz                                                                                                                                                                     |
|                            |                              | Operational conditions            |                                                                                                                                                                                |
|                            |                              | Operating temperature (T-T)       | -10 - 55 °C                                                                                                                                                                    |
|                            |                              | Operating relative humidity (H-H) | 10 - 39%                                                                                                                                                                       |
|                            |                              | Storage temperature (T-T)         | -20 - 60 °C                                                                                                                                                                    |
|                            |                              | Technical details                 |                                                                                                                                                                                |
|                            |                              | Compliance certificates           | Federal Communications Commission (FCC)                                                                                                                                        |
| Weight & dimensions        |                              |                                   |                                                                                                                                                                                |
|                            |                              | Width                             | 375 mm                                                                                                                                                                         |
|                            |                              | Depth                             | 329.3 mm                                                                                                                                                                       |
|                            |                              | Height                            | 53 mm                                                                                                                                                                          |
|                            |                              | Weight                            | 2.66 kg                                                                                                                                                                        |
|                            |                              | Package width                     | 451 mm                                                                                                                                                                         |
|                            |                              | Package depth                     | 147 mm                                                                                                                                                                         |
|                            |                              | Package height                    | 425 mm                                                                                                                                                                         |
|                            |                              | Package weight                    | 3.82 kg                                                                                                                                                                        |



6923172589828

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date