

## Dahua Technology WizMind DH-IPC-EBW8842-AS-IVC cámara de vigilancia Domo Cámara de seguridad IP Exterior 3280 x 2480 Pixeles Techo

Marca: Dahua Technology

Familia de productos: WizMind Código del producto: DH-IPC-

EBW8842-AS-IVC

Nombre del producto: DH-

IPC-EBW8842-AS-IVC

Dahua Technology WizMind DH-IPC-EBW8842-AS-IVC. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Domo. Ángulo de campo de visión (FOV): 185°, Ángulo de visión del objetivo, horizontal: 185°, Ángulo de visión del objetivo, vertical: 180°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 1.7 mm (1 / 1.7"). Distancia de detección: 27.9 m, Distancia de observación: 11.2 m, Distancia de reconocimiento: 5.6 m

Performance		Video	
Type *	IP security camera	Digital Wide Dynamic Range	<b>✓</b>
Placement supported *	Outdoor	(DWDR) Smart IR	<b>/</b>
Connectivity technology *	Wired	Smart IK	•
People counting function	✓	Audio	
Maximum operating distance	27.9 m	Audio input channels	1 channels
Wide Dynamic Range (WDR)	✓	Audio formats supported	G.711, G.722, G.723, G.726, PCM
Day/night mode	✓	Signal-to-Noise Ratio (SNR)	56 dB
Alarm input/output	×	Built-in microphone	<b>/</b>
Dynamic range	56 dB	Voice codecs	G.711Mu, G.711a, G.723, G.726, PCM
Design		Audio detection	✓
Form factor *	Dome		
Mounting type *	Ceiling	Network	
Product colour *	White	Ethernet LAN *	✓
Housing material	Metal		IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP;
International Protection (IP) code	IP67	Supported network protocols	SFTP; DHCP; DNS; DDNS; QoS;
IK code	IK10		UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Camera		Wi-Fi *	X
Camera pan control	×	Bluetooth *	×
Camera tilt control	×	Number of users	20 user(s)
Minimum illumination	0 lx	Streaming method	Multicast
Field of view (FOV) angle	185°	Live view	✓
Lens viewing angle, horizontal	185°	Number of simultaneous live view	
Lens viewing angle, vertical	180°	channels	3 channels
White balance	Auto, Custom modes, Manual, Natural, Outdoor, Street lamp	Websers	IE: IE11, IE10 Chrome:
Camera shutter type	Electronic	Web servers supported	48.0.2564.116 Firefox: 48.0.2 Edge 42.17134.1.0
Camera shutter speed	1/3 -1/100,000	Storage	
Adjustment shutter speed	Auto/Manual	-	
Image sensor		Built-in HDD *	X
Optical sensor size	25.4 / 1.7 mm (1 / 1.7")	Card reader integrated	✓ Minus CD (Turner Floorly)
Progressive scan	<b>✓</b>	Compatible memory cards	MicroSD (TransFlash) 256 GB
Sensor type *	CMOS	Maximum memory card size Internal memory	4000 MB
Panoramic camera		ROM capacity	2000 MB
Digital Wide Dynamic Range		Ports & interfaces	
(DWDR) (panoramic camera)	✓	Ethernet LAN (RJ-45) ports	1
Lens system		Microphone in	1 ✓
Number of lenses *	1	Microphone III	•
Detect distance	27.9 m		

Security				
Recognize distance         5.6 m         Alarm output channels         2           Maximum aperture number         2.8 m         Wilch in siren         ✓           Elked food length         1.29 mm         Security algorithms         HTTPS           Closest focusing distance         1.29 mm         Security algorithms         HTTPS           Night vision         Intelligent Video Surveillance (US)         Thursion, People counting, Tripwine system features           Night vision distance         1.0 m         Motion sensor         ✓           LED type         1.0 m         Motion sensor         ✓           Number of illumination LEDs         3.0 Cay 2480 pixels         Web-based management         ✓           Video         Maximum resolution*         3.280 x 2480 pixels         Meb-based management         ✓           Video compression formats         8 MP         Web browser         Somart PSS; DSS; DMSS           Video compression formats         4.264, H.264H, H.265, M-JPEG         Mosagement software         Somart PSS; DSS; DMSS           Video cording         4.264, H.264H, H.265, M-JPEG         Mover consumption (Power over corosumption (Power ove	Lens system		Security	
Maximum aperture number         2.2 m         Video motion detection         ✓           Identify distance         2.8 m         Video motion detection         ✓           Excel focal leght         1.29 mm         Security algorithms         HTTPS           Riyst vision         Intelligent Video Surveillance (IVS) system features         Video Common Security system features           Number of illumination LEDs         18 m         Mirror         ✓           Number of illumination LEDs         280 x 2480 pixels         Mirror         ✓           Wideo         Web-based management         ✓           Video formats supported         1,264, H.265, M.JPEG         Management software         ✓           Video compression formats         1,264, H.264H, H.265, M.JPEG         Mover         Video compression formats         Power           Video compression formats         1,264, H.264H, H.265, M.JPEG         Mover source type *         Po CP CP           Video compression formats         1,264, H.264H, H.265, M.JPEG         Mover source type *         Power source type *	Observe distance		Alarm input channels	
Identify distance	3		Alarm output channels	2
Fixed focal length         1.29 mm         Security algorithms         HTTPS           Closest focusing distance         0.2 m         HTTPS encryption         *           Night vision         y         Intelligent Video Surveillance (IVS)         Intrusion, People counting, Tripwire intrusion (Post System features)           Night vision distance         10 m         Micros ensor         *           Number of illumination LEDS         18 m         Micros (Micros)         *           Maximum resolution*         3280 x 2480 pixels         Web-based management         *           Maximum resolution*         4.264, H.265, M-JPEG         Management software         *           Video formats supported         H.264, H.265, M-JPEG         Management software         *           Video formats supported         H.264, H.265, M-JPEG         Menagement software         *           Video compression formats         H.264, H.265, M-JPEG         Power         *           Video compression formats         H.264, H.265, M-JPEG         Power         *           Video compression formats         H.264, H.265, M-JPEG         Power         *           Video compression formats         John Security algorithms         1,0         5,0           Video transition formats         Length Security algorithms         1,0<	'		Built-in siren	<b>✓</b>
Closest focusing distance	•		Video motion detection	✓
Night vision         Intelligent Video Surveillance (IVS) system features system features system features         Intrusion, People counting, Tripwine system features           Night vision distance         10 m         Motion sensor         ✓           LED type         IR         Mirror         ✓           Number of illumination LEDs         3 a         Digest authentication         ✓           Video         Sussain authentication         ✓         Certain authentication         ✓           Video formats supported         16.264, 12.655, M-JPEG         Management software         ✓         Smart PSS; DSS; DMSS           Video compression formats         14.264, 12.265, M-JPEG         Management software         DC, PoE           Video compression formats         14.264, 12.265, M-JPEG         Management software         DC, PoE           Video compression formats         14.264, 12.265, M-JPEG         Power         Dower         DC, PoE           Video compression formats         14.264, 12.265, M-JPEG         Power         Dower         DC, PoE           Video crooring         14.264, 12.265, M-JPEG         Power         Power         DC, PoE           Video recording         2         Power consumption (floption)         13 W           Video streaming         2         Country to video         12 P<	•		Security algorithms	HTTPS
Night vision*         v         system features         Intrusion, People counting, Tripwine           Night vision distance         10 m         Motion sensor         v           LED type         IR         Mirror         v           Number of illumination LEDs         3         Digest authentication         v           Video         Total megapixels*         8 MP         Web-based management         v           Video formats supported         H.264, H.265, M.JPEG         Management software         ymart PSS; DSS; DMSS           Video formats supported organics resolutions         704 x 576, 1280 x 960, 1536 x 2048, 2040, 352 x 288, 704 x 480, 2048, 2048, 2880 x 2160, 3280 x 2048         Power         Power           Supported graphics resolutions         704 x 576, 1280 x 960, 1536 x 2048, 2040, 2048, 2040, 2048, 2040, 2048, 2040, 2048, 2040, 2049, 20	J	0.2 m	HTTPS encryption	✓
Night vision distance 10 m Motion sensor	Night vision			Intrusion, People counting, Tripwire
Night vision distance    ED type	Night vision *	✓	•	
Number of illumination LEDs 3 3 Digest authentication	Night vision distance	10 m		
Video     Management features       Maximum resolution *     3280 x 2480 pixels     Web-based management     ✓       Total megapixels *     8 MP     Web browser     ✓       Video formats supported     H.264, H.265, M.JPEG     Management software     Smart PSS; DSS; DMSS       Video compression formats     352 x 240, 352 x 288, 704 x 480, 2048, 2048, 2048, 2880 x 2160, 3280 x 2048     Power     DC, PoE Power consumption (typical) 6.5 W       Video recording     ✓     Power consumption (Power over Ethernet (PoE))     13.9 W       Video intelligence analytic     ✓     DC output voltage     12       Video streaming     ✓     Doerational conditions     13.9 W       Noise reduction     ✓     Operating temperature (T-T)     -40 - 55 °C       Noise reduction technology     3D noise reduction     Operating temperature (T-T)     -30 - 70 °C       Gain control type     Auto     Storage temperature (T-T)     -30 - 70 °C       Gain control type     Output voltage     15 cm       Bit rate control     Constant Bit Rate (CBR)/Variable Bit Rate (VBR)     Midth     59.8 mm       Bit rate     3 - 16384     Width     59.8 mm       Back Light Compensation (HLC)     ✓     Diameter     15 cm       Highlight Compensation (HLC)     Fackaging data     1.21 kg       Package weight	• •			•
Maximum resolution * 3280 x 2480 pixels Web-based management	Number of illumination LEDs	3	Digest authentication	<b>*</b>
Total megapixels * 8 MP Web browser	Video		Management features	
Video formats supported Video compression formats Video recording Video recording Video recording Video recording Video intelligence analytic Video intelligence analytic Video streaming Video streamin	Maximum resolution *	•	Web-based management	✓
Video compression formats       H.264, H.264H, H.265, M-JPEG       Power         Supported graphics resolutions       352 x 240, 352 x 288, 704 x 480, 704 x 576, 1280 x 906, 1536 x 2048 2048 2048 2048 2048 2048 2048 2048	Total megapixels *	8 MP	Web browser	✓
Supported graphics resolutions 252 x 240, 352 x 288, 704 x 480, 704 x 576, 1280 x 960, 1536 x 2048, 2880 x 2160, 3280 x 2048  Video recording	• •	· · · · ·	Management software	Smart PSS; DSS; DMSS
Supported graphics resolutions704 x 576, 1280 x 960, 1536 x 2048, 2880 x 2160, 3280 x 2048Power consumption (typical) power consumption (typical)DC, PoEVideo recording4Power consumption (max)13 WFrame rate30 fpsPower consumption (Power over Ethernet (PoE))13.9 WVideo intelligence analytic4DC output voltage12Video streaming4Operational conditionsNoise reduction3D noise reductionOperating temperature (T-T)-40 - 55 °CGain control typeAutoStorage temperature (T-T)-30 - 70 °CBit rate controlConstant Bit Rate (CBR)/Variable Bit Rate (VBR)Operating relative humidity (H-H)0 - 95%Bit rate3 - 16384Width59.8 mmHighlight Compensation (BLC)4Diameter15 cmHighlight Compensation (HLC)4Packaging data1.21 kgPackage weight1.21 kgSustainabilityCompliance certificatesCE, Federal Communications Commission (FCC)	Video compression formats	•	Power	
Video recording Frame rate Video intelligence analytic Video intelligence analytic Video intelligence analytic Video streaming	Supported graphics resolutions		Power source type *	DC PoF
Video recording       Very and pract of the proper rate       Power consumption (max)       13 W         Video intelligence analytic       Very and proper consumption (Power over Ethernet (PoE))       13.9 W         Video streaming       Very analytic       DC output voltage       12         Noise reduction       Very actional conditions       Very actional conditions         Noise reduction technology       3D noise reduction       Operating temperature (T-T)       -40 - 55 °C         Gain control type       Auto       Storage temperature (T-T)       -30 - 70 °C         Bit rate control       Constant Bit Rate (CBR)/Variable Bit Rate (VBR)       Operating relative humidity (H-H)       0 - 95%         Bit rate       3 - 16384       Weight & dimensions       15 cm         Highlight Compensation (BLC)       Very action gradient properties of the proper	Supported grapmes resolutions			•
Video intelligence analytic  Video streaming  Video strea	Video recording	✓	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Video streaming  Video	Frame rate	30 fps	Power consumption (Power over	12 0 W
Noise reduction  Noise reduction technology  Gain control type  Bit rate control  Bit rate  Back Light Compensation (BLC)  Highlight Compensation (HLC)  Figh Lage Lage Lage Lage Lage Lage Lage Lage	Video intelligence analytic	✓		
Noise reduction technology  Gain control type  Auto  Constant Bit Rate (CBR)/Variable Bit rate control  Bit rate  Back Light Compensation (BLC)  Highlight Compensation (HLC)  Fackaging data  Packaging data  Packaging content  Centrol type  Auto  Operating temperature (T-T)  -30 - 70 °C  Operating relative humidity (H-H)  0 - 95%  Weight & dimensions  Width  59.8 mm  Diameter  Weight  790 g  Packaging data  Package weight  1.21 kg  Sustainability  Compliance certificates  CE, Federal Communications Commission (FCC)  Packaging content	Video streaming	✓	DC output voltage	12
Gain control type Bit rate control Bit rate control Bit rate Back Light Compensation (BLC) Highlight Compensation (HLC)  Fig. 1	Noise reduction	✓	Operational conditions	
Bit rate control  Bit rate control  Bit rate  Constant Bit Rate (CBR)/Variable Bit Rate (VBR)  Bit rate  Back Light Compensation (BLC)  Highlight Compensation (HLC)  Formula (March Meight (March Mei	Noise reduction technology	3D noise reduction	Operating temperature (T-T)	-40 - 55 °C
Bit rate Control  Bit rate  3 - 16384  Weight & dimensions  Width  59.8 mm  Diameter  15 cm  Weight  Packaging data  Package weight  Sustainability  Compliance certificates  CE, Federal Communications Commission (FCC)  Packaging content	Gain control type	Auto	Storage temperature (T-T)	-30 - 70 °C
Bit rate  Back Light Compensation (BLC) Highlight Compensation (HLC)  Fackaging data  Package weight  Sustainability  Compliance certificates  CE, Federal Communications Commission (FCC)  Packaging content	Bit rate control		Operating relative humidity (H-H)	0 - 95%
Back Light Compensation (BLC) Highlight Compensation (HLC)  Packaging data Package weight  Sustainability  Compliance certificates  CE, Federal Communications Commission (FCC)  Packaging content	Bit rate		Weight & dimensions	
Diameter Weight 790 g  Packaging data Package weight 1.21 kg  Sustainability  Compliance certificates CE, Federal Communications Commission (FCC)  Packaging content	Back Light Compensation (BLC)	<b>√</b>	Width	59.8 mm
Packaging data Package weight Sustainability Compliance certificates CE, Federal Communications Commission (FCC) Packaging content	-	/	Diameter	15 cm
Package weight  Sustainability  Compliance certificates  CE, Federal Communications Commission (FCC)  Packaging content	riiginight compensation (nec)	•	Weight	790 g
Sustainability  Compliance certificates  CE, Federal Communications Commission (FCC)  Packaging content			Packaging data	
Compliance certificates  CE, Federal Communications Commission (FCC)  Packaging content			Package weight	1.21 kg
Compliance certificates  Commission (FCC)  Packaging content			Sustainability	
			Compliance certificates	·
Number of cameras * 1			Packaging content	
			Number of cameras *	1



6923172507655

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.