



## Dahua Technology DH-PTZ85848-HNF-PA-FL cámara de vigilancia Bala (forma) Interior y exterior 3840 x 2160 Píxeles Techo/pared

**Marca :** Dahua Technology

**Código del producto:** DH-PTZ85848-HNF-PA-FL

**Nombre del producto :** DH-PTZ85848-HNF-PA-FL

Dahua Technology DH-PTZ85848-HNF-PA-FL. Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico, Protocolos PTZ: DH-SD, Pelco-P/D. Tipo de montaje: Techo/pared, Color del producto: Gris, Factor de forma: Bala (forma). Ángulo de rotación: 180°, Ángulo de visión del objetivo, horizontal: 64.9°, Ángulo de visión del objetivo, vertical: 38°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 1.8 mm (1 / 1.8"). Zoom óptico: 48x, Zoom digital: 16x, Distancia de detección: 6000 m

| Performance                        |   | Video                             |   |
|------------------------------------|---|-----------------------------------|---|
| Placement supported *              | Indoor & outdoor                            | Back Light Compensation (BLC)     | ✓   |
| Connectivity technology *          | Wired                                       | Highlight Compensation (HLC)      | ✓   |
| PTZ protocols                      | DH-SD, Pelco-P/D                            | Digital Wide Dynamic Range (DWDR) | ✓   |
| Day/night mode                     | ✓   | Region of Interest (ROI) encoding | ✓   |
| Design                             |   | Audio                             |   |
| Form factor *                      | Bullet                                      | Audio input channels              | 1 channels  |
| Mounting type *                    | Ceiling/wall                                | Audio output channels             | 1 channels  |
| Product colour *                   | Grey  | Signal-to-Noise Ratio (SNR)       | 55 dB   |
| International Protection (IP) code | IP67  | Voice codecs                      | G.711Mu, G.711a, G.726, PCM   |
| Camera                             |   | Network                           |   |
| Angle of rotation                  | 180°  | Ethernet LAN *                    | ✓   |
| Lens viewing angle, horizontal     | 64.9°                                       | Supported network protocols       | HTTP; HTTPS; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; QoS; FTP; UPnP; ICMP; SNMP; IGMP; RTP; PPPoE; RTMP; TCP |
| Lens viewing angle, vertical       | 38°   |                                   |   |
| Lens viewing angle, diagonal       | 71.3°                                       | Wi-Fi *                           | ✗   |
| Tilt angle range                   | -45 - 90°                                   | Bluetooth *                       | ✗   |
| Pan range                          | 0 - 360°                                    | Number of users                   | 20 user(s)  |
| Pan speed                          | 160 °/sec                                   | Streaming method                  | Multicast   |
| White balance                      | Auto, Manual, Natural, Outdoor, Street lamp | Storage                           |   |
| Camera shutter speed               | 1/1 s-1/30,000                              | Compatible memory cards           | MicroSD (TransFlash)  |
| Number of Privacy masking areas    | 24  | Maximum memory card size          | 512 GB  |
| Image sensor                       |   | ROM capacity                      | 8000 MB   |
| Optical sensor size                | 25.4 / 1.8 mm (1 / 1.8")                    | RAM capacity                      | 2000 MB   |
| Sensor type *                      | CMOS  | Ports & interfaces                |   |
| Lens system                        |   | Ethernet LAN (RJ-45) ports        | 1   |
| Zoom capability                    | ✓   | RS-485 ports                      | 1   |
| Optical zoom                       | 48x   | Security                          |   |
| Digital zoom                       | 16x   | Alarm input channels              | 7   |
| Number of lenses *                 | 1   | Alarm output channels             | 2   |
| Detect distance                    | 6000 m                                      | Video motion detection            | ✓   |
| Observe distance                   | 2381 m                                      | Power                             |   |
| Recognize distance                 | 1200 m                                      | Power source type *               | DC  |
| Focal length range                 | 6.25 -300                                   | Power consumption                 | 22 mA   |
| Identify distance                  | 600 m                                       | Power consumption (max)           | 63 W  |
| Night vision                       |   | Operational conditions            |   |
| Night vision *                     | ✓   | Operating temperature (T-T)       | -40 - 70 °C   |
| Night vision distance              | 1000 m                                      | Operating relative humidity (H-H) | 0 - 95%   |
| Video                              |   |                                   |   |
| Maximum resolution *               | 3840 x 2160 pixels                          |                                   |   |
| Total megapixels *                 | 8 MP  |                                   |   |

| Video                      |   | Weight & dimensions |          |
|----------------------------|---|---------------------|----------|
| Video formats supported    | H.264, H.265                                    | Width               | 252.2 mm |
| Video compression formats  | H.264H, H.264M, MPEG2                           | Depth               | 344.6 mm |
| Video streaming            | ✓   | Height              | 499.8 mm |
| Noise reduction            | ✓   | Weight              | 15.4 kg  |
| Noise reduction technology | 2D noise reduction, 3D noise reduction          | Packaging data      |          |
| Bit rate control           | Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Package weight      | 23.7 kg  |
|                            |   | Packaging content   |          |
|                            |   | Number of cameras * | 1        |
|                            |   | Wiper included      | ✓        |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date