

Dahua Technology DH-PTZ85448-HNF-PA cámara de vigilancia Bala (forma) Interior y exterior 2560 x 1440 Pixeles Techo/pared

Marca : Dahua Technology

Código del producto: DH-PTZ85448-HNFPA

Nombre del producto: DH-PTZ85448-HNF-PA

Dahua Technology DH-PTZ85448-HNF-PA. Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico, Protocolos PTZ: DH-SD, Pelco-P/D. Tipo de montaje: Techo/pared, Color del producto: Gris, Factor de forma: Bala (forma). Ángulo de rotación: 180°, Ángulo de visión del objetivo, horizontal: 62.36°, Ángulo de visión del objetivo, vertical: 36.55°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 1.8 mm (1 / 1.8"). Zoom óptico: 48x, Zoom digital: 16x, Distancia de detección:

Danis anno an		Wide	
Performance		Video	
Placement supported * Connectivity technology * PTZ protocols Day/night mode	Indoor & outdoor Wired DH-SD, Pelco-P/D	Back Light Compensation (BLC) Highlight Compensation (HLC) Digital Wide Dynamic Range (DWDR)	* *
Design		Region of Interest (ROI) encoding	✓
Form factor *	Bullet	Audio	
Mounting type * Product colour * International Protection (IP) code Camera	Ceiling/wall Grey IP67	Audio input channels Audio output channels Signal-to-Noise Ratio (SNR) Voice codecs	1 channels 1 channels 55 dB G.711Mu, G.711a, G.726, PCM
Angle of rotation	180°	Network	
Lens viewing angle, horizontal	62.36°	Ethernet LAN *	✓
Lens viewing angle, vertical Lens viewing angle, diagonal Tilt angle range Pan range	36.55° 69.76° -45 - 90° 0 - 360°	Supported network protocols	HTTP; HTTPS; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; QoS; FTP; UPnP; ICMP; SNMP; IGMP; RTP; PPPoE; RTMP; TCP
Pan speed	160 °/sec	Wi-Fi *	×
White balance	Auto, Manual, Natural, Outdoor,	Bluetooth *	X
Camera shutter speed	Street lamp 1/1 s-1/30,000	Number of users Streaming method	20 user(s) Multicast
Number of Privacy masking areas	24	Storage	Halicast
Image sensor		Compatible memory cards	MicroSD (TransFlash)
Optical sensor size Sensor type *	25.4 / 1.8 mm (1 / 1.8") CMOS	Maximum memory card size ROM capacity	512 GB 8000 MB
Lens system		RAM capacity	2000 MB
Zoom capability	✓	Ports & interfaces	_
Optical zoom	48x	Ethernet LAN (RJ-45) ports RS-485 ports	1
Digital zoom Number of lenses *	16x 1	Security	1
Detect distance	6000 m	Alarm input channels	7
Observe distance	2381 m	Alarm output channels	2
Recognize distance	1200 m	Video motion detection	✓
Focal length range Identify distance	6.25 -300 600 m	Power	
Night vision	000 III	Power source type *	DC
Night vision *	✓	Power consumption	22 mA
Night vision distance	400 m	Power consumption (max)	63 W
Video		Operational conditions	
Maximum resolution * Total megapixels *	2560 x 1440 pixels 4 MP	Operating temperature (T-T) Operating relative humidity (H-H)	-40 - 70 °C 0 - 95%

Video		Weight & dimensions	
Video formats supported	H.264, H.265	Width	252.2 mm
Video compression formats	H.264H, H.264M, MPEG2	Depth	344.6 mm
Video streaming	✓	Height	499.8 mm
Noise reduction	✓	Weight	15.4 kg
Noise reduction technology	2D noise reduction, 3D noise reduction	Packaging data	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Package weight	23.7 kg
		Packaging content	
		Number of cameras *	1
		Wiper included	✓

