



ATEN VS82H divisor de vídeo HDMI 2x HDMI

Marca : ATEN

Código del producto: VS82H

Nombre del producto : Distribuidor HDMI True 4K de 2 puertos

18 Gb/s, 600 MHz, 2x HDMI, HDCP, 88x60x150 mm

ATEN VS82H divisor de vídeo HDMI 2x HDMI:

El distribuidor VS82H de ATEN le ofrece una resolución de vídeo superior de 4K real y una calidad sin pérdida al enviar una fuente de vídeo de alta definición digital a dos pantallas. Admite equipos con HDMI desde reproductores DVD y decodificadores de satélite hasta todas las pantallas HDMI.

Aparte de ser compatible con HDCP 2.2, el VS82H incluye detección EDID automática que siempre presenta a los usuarios la mejor resolución en diferentes pantallas. Además de la compatibilidad con el canal de audio DTS-HD Master 7.1 y Dolby TrueHD, el VS82H garantiza una calidad de audio increíble y sin distorsión.

Y lo que es más, el VS82H es un distribuidor con alimentación por bus que se puede cargar directamente desde un dispositivo conectado a través del puerto Micro-USB. Al integrar las funciones anteriores, le ofrece una solución efectiva para aplicaciones personales, empresariales, educativas y comerciales.



Ports & interfaces		Packaging data	
Video port type *	HDMI	Quantity per pack	1 pc(s)
Video out *	2x HDMI	Package width	59 mm
HDMI version	2.0	Package depth	119 mm
Video ports quantity *	2	Package height	160 mm
Features		Package weight	196 g
Product colour	Black	Packaging content	
Housing material	Aluminium	Manual	✓
Maximum resolution *	4096 x 2160 pixels	Cables included	Micro-USB
HD type	4K Ultra HD	Operational conditions	
3D	✓	Operating temperature (T-T)	0 - 40 °C
Maximum operating distance	5 m	Storage temperature (T-T)	-20 - 60 °C
Maximum refresh rate	60 Hz	Operating relative humidity (H-H)	0 - 80%
Bandwidth	600 MHz	Storage relative humidity (H-H)	0 - 80%
HDCP version	2.2	Logistics data	
LED indicators	Status	Master (outer) case net weight	4.8 kg
Dolby technologies	DTS-HD Master Audio, Dolby TrueHD	Harmonized System (HS) code	85176990
Power		Master (outer) case width	315 mm
AC input voltage	5 V	Master (outer) case length	490 mm
Power consumption (typical)	1.35 W	Master (outer) case height	338 mm
USB powered	✓	Master (outer) case gross weight	8.36 kg
Weight & dimensions		Products per master (outer) case	40 pc(s)
Width	60 mm		
Depth	150 mm		
Height	88 mm		
Weight	120 g		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date