## Epson OmniLink TM-T88VII 180 x 180 DPI Alámbrico Térmico Impresora de TPV

Marca : Epson Código del producto: C31CJ57032

Nombre del producto: OmniLink TM-T88VII

Impresora Térmica de Recibos TM-T88VII

Epson OmniLink TM-T88VII. Tecnología de impresión: Térmico, Tipo: Impresora de TPV, Resolución máxima: 180 x 180 DPI. Grosor de la impresión: 48 - 80 μm, Máximo diámetro del rollo: 8.3 cm, Ancho de papel soportado: 80 mm. Tecnología de conectividad: Alámbrico, Conector USB: USB Type-A / USB Type-B, Conectividad opcional: LAN inalámbrica. Ethernet LAN, velocidad de transferencia de datos: 10,100 Mbit/s. Código de barras incorporado: CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A,..., Nivel de presión sonora (imprimiendo): 52 Db, Nivel de presión sonora (en espera): 52 Db





Printing		Design	
Maximum resolution 180 x 180 D	30 DPI	Product colour *	Black
	500 mm/sec 1.41 x 3.39 mm Text, Graphic, Barcode, 2D barcode ANK Thermal POS printer	Power	
Printing characters Text, Gr Character sets ANK Print technology * Thermal		Power source type * Power consumption Power consumption (standby) Power consumption (standby)	USB 27900 mA 1400 mA 1.4 W
Paper handling		Operational conditions	
Printing media thickness 48 - 80 p  Maximum roll diameter 8.3 cm  Supported paper width 80 mm	um	Operating temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	5 - 45 °C 10 - 90% 10 - 90%
Media thickness 48 - 80 r	mm	System requirements	
Ports & interfaces		Pre-installed software	Server Direct Print, ePOS-Device, ePOS-Display, ePOS-Print
USB port *  USB connector  Parallel connector  Connectivity technology *  Wired	oe-A / USB Type-B	Weight & dimensions Width Depth Height	145 mm 195 mm 148 mm
Optional connectivity Wireless	LAN	Weight	1.7 kg
Network		Packaging data	
Ethernet LAN *  Ethernet LAN data rates 10,100 M  Wi-Fi *  X	Mbit/s	Quantity per pack Package width Package depth	1 pc(s) 195 mm 235 mm
Features		Package height	260 mm
Ruilt-in barcodes * (A/B/C),	AR (NW-7), Code 128 Code 39, Code 93, EAN13, S1 DataBar, GS1-128, ITF, JPC-E	Package weight  Print technology  Column capacity	2.7 kg 42/56

Features		Logistics data	
Sound pressure level (printing)	52 dB	Pallet weight (UK)	0 g
Sound pressure level (standby)	52 dB	Products per pallet	112 pc(s)
Mean time between failures (MTBF)	360000 h	Pallet gross weight	0 g
Autocutter durability	3 million cuts	Products per pallet (UK)	168 pc(s)
Paper save function	✓	Technical details	
Print head life	200 km	Changeable interface	<b>✓</b>
Mounting position	Horizontal/Vertical	Lifetime	20000000 lines
Wall mountable	✓		
Built-in sensors details	Paper End Sensor, Paper Near End Sensor, Cover Open Sensor, Receipt paper sensor CE	Other features	
		Buffer size	4 KB
Certification		Mean cycles between failures (MCBF)	70000000

