## Canon

## Canon EOS R8 MILC 24.2 MP CMOS 6000 x 4000 Pixeles Negro

Marca : Canon Familia de productos: EOS Código del producto: 5803C002

Nombre del producto : EOS

R8

## EOS R8 Cuerpo

Canon EOS R8. Tipo de cámara: MILC, Megapixeles: 24.2 MP, Tipo de sensor: CMOS, Máxima resolución de imagen: 6000 x 4000 Pixeles. Sensibilidad ISO (máx.): 204800. Velocidad máxima del obturador: 1/16000 s. Wifi. Tipo HD: 4K Ultra HD, Máxima resolución de video: 3840 x 2160 Pixeles. Pantalla táctil. Tipo de visor de imagen: Electrónico. Peso: 414 g. Color del producto: Negro





Picture quality		Viewfinder	
Image sensor aspect ratio Camera type *	3:2 MILC	Viewfinder frame rate (power saving 60 fps mode)	
Megapixel (approx.) *	24.2 MP	Viewfinder frame rate (smooth	120 fps
Sensor type *	CMOS	mode)	·
Sensor cleaning system	Ultrasonic vibration 6000 x 4000 pixels EOS Integrated Cleaning System 6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600	Viewfinder resolution (approx.)	2360000 pixels
Maximum image resolution *		Ports & interfaces	
Sensor cleaning system name		USB version * USB connector	3.2 Gen 2 (3.1 Gen 2) USB Type-C
Still image resolution(s) *		HDMI * HDMI connector type	<b>✓</b> Micro
		Microphone in	✓
Image stabilizer *	×	Headphone outputs	1
Supported aspect ratios	1:1, 3:2, 4:3, 16:9	Headphone connectivity	3.5 mm
Image sensor size (W x H)	35.9 x 23.9 mm	Network	
Sensor format	Full-frame	Bluetooth *	<b>✓</b>
Built-in low-pass filter	IDEC DAW C DAW HEIE	Bluetooth version	4.2
Image formats supported *	JPEG, RAW, C-RAW, HEIF	Bluetooth Low Energy (BLE)	<b>✓</b>
Lens system		Wi-Fi *	<b>✓</b>
Lens mount interface	Canon RF	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Focusing		Camera	
Focus *	ΠL		Auto, Cloudy, Custom modes,
Focus adjustment *  Auto focusing (AF) modes *	Auto/Manual Continuous Auto Focus, One Shot	White balance *	Daylight, Flash, Fluorescent, Manual, Shade, Tungsten
Auto rocusing (Ar / modes	Focus, Servo Auto Focus		Children, Close-up (macro), Food,
Auto Focus (AF) object detection	Aircraft, Animal, Bird, Body, CAT, Dog, Eye, Face, Head, Horse, People, Train, Vehicle	Scene modes *	Group photo, HDR backlight control, Handheld night scene, Landscape, Panning, Panorama, Portrait, Self-
Face tracking	✓		portrait, Silent shutter, Sports  Aperture priority, Auto, Flexible
Auto Focus (AF) lock	✓	Shooting modes *	priority, Manual, Program, Scene,
Auto Focus (AF) assist beam	✓		Shutter priority
Exposure		Self-timer delay *	2,10 s
ISO sensitivity (min) *	50	Dioptre correction	<b>✓</b>
ISO sensitivity (max) *	204800	Diopter adjustment (D-D)	-4 - 1
		Histogram	<b>✓</b>
		Live view	✓

Exposure		Camera	
poom.o	100, 200, 400, 800, 1600, 3200,	Direct printing	1
ISO sensitivity	6400, 12800, 25600, 51200,	GPS (satellite)	×
	102400, Auto Aperture priority AE, Auto, Manual,	Orientation sensor	<i>y</i>
Light exposure modes *	Shutter priority AE	Anti-dust function	1
Light exposure control	Program AE	Smartphone/tablet remote support	1
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)	View on smartphone	<b>✓</b>
Light metering *	Centre-weighted, Evaluative (Multipattern), Spot	Highlight alert	/
Auto Exposure (AE) lock	✓	Tripod mounting supported *	✓
Number of measurement zones	384	Image processor	DIGIC X
Shutter		Design	
Fastest camera shutter speed *	1/16000 s	Product colour *	Black
Slowest camera shutter speed *	30 s	Dustproof	<b>✓</b>
Camera shutter type	Electronic	Splash proof	<b>✓</b>
Flash		Battery	
Flash exposure lock	✓	Battery technology *	Lithium-lon (Li-lon)
External flash connector	✓	Battery type	LP-E17
Flash exposure compensation	✓	Number of batteries supported	1
Flash exposure correction	±3EV (1/3 EV step)	Battery level indicator	✓
Shoe mounting point Shoe mounting point type	✓ Hot shoe	Power	
2	Hot shoe	USB Type-C charging port *	✓
Video Video recording *	<b>✓</b>	USB Type-C required charging power (min) *	7.5 W
Maximum video resolution *	3840 x 2160 pixels	USB Type-C required charging power (max) *	7.5 W
HD type * Video resolutions	4K Ultra HD 1920 x 1080,3840 x 2160 pixels	Operational conditions	
Video formats supported	H.264, H.265	Operating temperature (T-T)	0 - 40 °C
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit	Weight & dimensions	
Audio		Width	132.5 mm
Built-in microphone *	✓	Depth	70 mm
Built-in speaker(s)	✓	Height	86.1 mm
Audio system	stereo	Weight	414 g
Wind filter	✓	Weight (including battery)	461 g
Audio formats supported	LPCM, AAC	Packaging data	
Memory		Quantity per pack Package width	1 pc(s) 192 mm
Compatible memory cards *	SD, SDHC, SDXC	Package depth	282 mm
Memory slots	1	Package height	153 mm
Display		Package weight	1.16 kg
Display *	LCD	Packaging content	
Touchscreen *	<b>✓</b>	Neck strap included	✓
Display diagonal (metric)	7.5 cm	AC adapter included *	×
Display resolution Display aspect ratio	1620000 dot 3:2	Battery charger included	✓
Vari-angle LCD display	√.	Batteries included	✓
Viewfinder		Logistics data	
Viewfinder type	Electronic	Products per pallet	72 pc(s)
Magnification	0.7x		
Viewfinder screen size	0.39"		

