



## Canon EOS R6 Mark II Cuerpo MILC 24.2 MP CMOS 6000 x 4000 Píxeles Negro

Marca : Canon

Familia de productos: EOS

Código del producto:  
5666C003



Nombre del producto : R6  
Mark II

24.2 Mp, 35.9 x 23.9 mm CMOS, DIGIC X, Dual Pixel CMOS AF II, 0.5" OLED colour EVF, 3.0" Clear View LCD II, 2x SD/SDHC/SDXC, 588 g

Canon EOS R6 Mark II. Tipo de cámara: Cuerpo MILC, Megapíxeles: 24.2 MP, Tipo de sensor: CMOS, Máxima resolución de imagen: 6000 x 4000 Píxeles. Sensibilidad ISO (máx.): 102400. Velocidad máxima del obturador: 1/8000 s. Wifi. Tipo HD: 4K Ultra HD, Máxima resolución de video: 3840 x 2160 Píxeles. Diagonal de la pantalla: 7.62 cm (3"), Pantalla táctil. Tipo de visor de imagen: Electrónico. Peso: 588 g. Color del producto: Negro



<b>Picture quality</b>		<b>Viewfinder</b>	
Image sensor aspect ratio	3:2	Viewfinder screen size	0.5"
Camera type *	MILC Body	Viewfinder frame rate (power saving mode)	60 fps
Megapixel (approx.) *	24.2 MP	Viewfinder frame rate (smooth mode)	120 fps
Sensor type *	CMOS	Viewfinder information	AF method, AF operation, AF point information, Anti-flicker shooting, Aperture, Battery level, Electronic level, Exposure compensation, Exposure simulation, Focus distance scale, Grid, Highlight tone priority, Histogram, ISO speed, Image Quality, Metering mode, Picture Style, Shooting mode, Shutter speed, White balance
Sensor cleaning system	Ultrasonic vibration	Viewfinder resolution (approx.)	3690000 pixels
Maximum image resolution *	6000 x 4000 pixels	<b>Ports &amp; interfaces</b>	
Sensor cleaning system name	EOS Integrated Cleaning System	PictBridge *	✗
Still image resolution(s) *	6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 6000 x 3368, 3984 x 2240, 2976 x 1680, 2400 x 1344, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600, 4000 x 4000	USB version *	3.2 Gen 2 (3.1 Gen 2)
Image stabilizer *	✓	USB connector	USB Type-C
Supported aspect ratios	1:1, 3:2, 4:3, 16:9	HDMI *	✓
Image sensor size (W x H)	35.9 x 23.9 mm	HDMI connector type	Micro
Sensor format	Full-frame	Microphone in	✓
Built-in low-pass filter	✓	Headphone outputs	1
Sensor shift IS	✓	Headphone connectivity	3.5 mm
Sensor shift IS number of stops (max)	8	<b>Network</b>	
Image formats supported *	JPEG, RAW, C-RAW, HEIF	Bluetooth *	✓
<b>Lens system</b>		Bluetooth version	5
Lens mount interface	Canon RF	Bluetooth Low Energy (BLE)	✓
Mounting type	Bayonet	Wi-Fi *	✓
<b>Focusing</b>		Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Focus *	TTL	Near Field Communication (NFC) *	✗
Focus adjustment *	Auto/Manual	<b>Camera</b>	
Auto focusing (AF) modes *	Continuous Auto Focus, One Shot Focus, Servo Auto Focus	White balance *	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Shade, Tungsten
Auto Focus (AF) object detection	Animal, Bird, Eye, Face, People, Vehicle		
Face tracking	✓		
Auto Focus (AF) lock	✓		
Auto Focus (AF) assist beam	✓		

<b>Exposure</b>		<b>Camera</b>	
ISO sensitivity (min) *	100	Custom white balance	✓
ISO sensitivity (max) *	102400	Scene modes *	Auto
ISO sensitivity	100, 125, 160, 200, 250, 320, 400, 640, 800, 1600, 2000, 2500, 3200, 4000, 5000, 6400, 8000, 10000, 12800, 16000, 25600, 32000, 40000, 51200, 102400	Shooting modes *	Aperture priority, Auto, Flexible priority, Intelligent auto, Manual, Program, Scene, Shutter priority
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE	Self-timer delay *	2,10 s
Light exposure control	Program AE	Subject recognition	✓
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)	Dioptre correction	✓
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot	Diopter adjustment (D-D)	-4 - 2
Auto Exposure (AE) lock	✓	Histogram	✓
Number of measurement zones	384	Live view	✓
Exposure bracketing (AEB)	± 3EV (1/2EV; 1/3EV stop)	Direct printing	✓
Anti-flicker shooting	✓	Orientation sensor	✓
<b>Shutter</b>		Anti-dust function	✓
Fastest camera shutter speed *	1/8000 s	Smartphone/tablet remote support	✓
Slowest camera shutter speed *	30 s	View on smartphone	✓
Camera shutter type	Mechanical	High Dynamic Range (HDR) supported	✓
Shutter speed settings	B	Colour space supported	RGB
<b>Flash</b>		Image crop aspect ratios	1:1, 3:2, 4:3, 16:9
Flash exposure lock	✓	Multiple exposure	✓
External flash connector	✓	RAW image processing	✓
Flash exposure compensation	✓	HEIF to JPEG conversion	✓
Shoe mounting point	✓	Camera drive modes	Continuous high, Continuous high+, Continuous low, Self-timer, Single
Shoe mounting point type	Hot shoe	Built-in interval timer	✓
Flash exposure bracketing	✓	Playback zoom (min)	1.5x
<b>Video</b>		Playback zoom number of steps	15
Video recording *	✓	Histogram options	Brightness
Maximum video resolution *	3840 x 2160 pixels	Highlight alert	✓
HD type *	4K Ultra HD	Tripod mounting supported *	✓
Video resolutions	1920 x 1080, 3840 x 2160 pixels	Image processor	DIGIC X
Video formats supported	H.264, H.265	<b>Design</b>	
Dual card video recording	✓	Product colour *	Black
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit	Dustproof	✓
<b>Audio</b>		Splash proof	✓
Built-in microphone *	✓	<b>Battery</b>	
Built-in speaker(s)	✓	Battery technology *	Lithium-Ion (Li-Ion)
Audio system	stereo	Battery type	LP-E6NH
Wind filter	✓	Number of batteries supported	1
Audio formats supported	LPCM, AAC	Battery level indicator	✓
Noise reduction	✓	Compatible power supply / battery chargers	PD-E1, LC-E6, DR-E6 + AC-E6N
<b>Memory</b>		<b>Operational conditions</b>	
Compatible memory cards *	SD, SDHC, SDXC	Operating temperature (T-T)	2 - 40 °C
Memory slots	2	<b>Weight &amp; dimensions</b>	
<b>Display</b>		Width	138.4 mm
Display *	LCD	Depth	88.4 mm
Touchscreen *	✓	Height	98.4 mm
Display diagonal *	7.62 cm (3")	Weight	588 g
Display diagonal (metric)	7.5 cm	Weight (including battery)	670 g
Display resolution	1620000 dot	<b>Packaging data</b>	
Display aspect ratio	3:2	Quantity per pack	1 pc(s)
Vari-angle LCD display	✓	<b>Packaging content</b>	
		Neck strap included	✓
		Battery charger included	✓

**Viewfinder**

Viewfinder type	Electronic
Magnification	0.76x

**Packaging content**

Batteries included	✓
--------------------	---

**Logistics data**

Products per pallet	96 pc(s)
---------------------	----------

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.